2. A Laboratory Scale Synthesis of Ethanol from Agricultural Waste as Bio-based Solvent for Waxy-Paraffinic Crude Oil Mitigation

591 (107 asia)
IOP Conference Series Materials Science and Engineering
on Robotics and Mechantronics
517
VeLENE 5 17 - 2019 8-11 Movember 2018
Singapore EDITOR Marri ka Ez
The open access journal for conference proceedings
lopscience.org/jpcs
IOP Publishing

Table of contents

Volume 854

2020

◆ Previous issue Next issue ▶

THE 2ND INTERNATIONAL CONFERENCE ON SCIENCE AND INNOVATED ENGINEERING 9 - 10 November 2019, Malacca, Malaysia

Accepted papers received: 28 April 2020 Published online: 01 July 2020

Open all abstracts

Preface			
OPEN ACCESS			011001
Preface			
+ Open abstract	Tiew article	🔁 PDF	
OPEN ACCESS			011002
Delegates			
	Tiew article	🔁 PDF	
OPEN ACCESS			011003
Peer review state	ement		
+ Open abstract	Tiew article	PDF	

Engineering & Technology

OPEN ACCESS			012001
The Mechanical F (FRPW) Compos	Performance of Pipe ites	e Based on Fiberglass Reinforced with Plastic Waste	
Noraini Marsi, Ling	eshavaran Subramania	am, Anika Zafiah Mohd Rus, Nurulsaidatulsyida Sulong,	
Muhammad Haikal	Mohd Fodzi, Nur Ath	irah Huzaisham, Nik Alnur Auli Nik Yusuf, Salwa Mahmood,	
Muhammad Farid S	haari and Hafizuddin	Hakim Shariff	
+ Open abstract	Tiew article	🔁 PDF	
OPEN ACCESS			012002
The Innovation of	Interlock Bricks	kith A Mixture of Bagasse Ash Without Combustione,	0
ZErwantri, DPA	Gowkies philip, M S A	Amin and F Darmawan	W

+ Open abstract	View article	🔁 PDF	
OPEN ACCESS Transesterificatio Zeolite/NaOH	n Condition of Cruc	de Palm Oil to Biodiesel Using Solid Catalyst	012003
E Kurniasih, P Pard	i and Adriana		
	View article	PDF	
OPEN ACCESS			012004
Effects of strain ralloy steel	ate due to SMAW v	velding on mechanical properties of AISI 1005 low	
Husaini, K Akbary,	I Hasanuddin, T E Put	tra and H Husin	
	Tiew article	PDF	
OPEN ACCESS Different Techniq and Installations	ues of Solar Rooftc	op Combo-PV/T System Implementation: Materials	012005
Suryati, Nelly Safitr	i, Misriana and Widdh	na Mellyssa	
+ Open abstract	Tiew article	🔁 PDF	
Black Liquor Pret Bioethanol Muryanto muryanto	treatment of Concor , Eka Mardika Handay	rb and Enzymatic Hydrolysis for Lignocellulosic yani and Yan Irawan	012006
	View article	PDF	
OPEN ACCESS Reliability Analy	sis of 20 KV Electri	ic Power Distribution System	012007
OPEN ACCESS Synthesis and Ch Surfactant-Induce	aracterization of Pd ed Electroless Platin	-Cu-Zr/Alumina Composite Membrane Using ng Technique	012008
Ratna Sari, Ratni De	ewi and Lukman Haki	m	
	View article	PDF	
OPEN ACCESS Development of a System for Monit	h High Performance Foring Performance	Remote Terminal Unit (RTU) of Wireless SCADA of Micro Hydro Power Plant	012009
Salahuddin, Bakhtia This site uses cookid ±cOperParbsara ctand	r, Yusman and Fadhli es. By continuing to us Coakiðsiewlargicle	se this site you agree to our use of cookies. To find out more, PDF	8

OPEN ACCESS A Review on the A	Air Flow Behaviou	r in the Intake Pipe	012010
J W Lim, N Narendr	an, C E Chai and M I	I N Ma'arof	
+ Open abstract	View article	🔁 PDF	
OPEN ACCESS			012011
Characterization of	of Fresh Sidoarjo N	Iud as Material on Geopolymer System	
Syarwan, Kiki Yolan	nda Putri, Ruhana, Mi	iswar and Amir Fauzi	
+ Open abstract	View article	🔁 PDF	
OPEN ACCESS Effect of POFA as	s a replacement ma	terial on fly ash based geopolymer mortar	012012
Mulizar, Fazliah, Isk	andar, Aiyub and An	nir Fauzi	
	View article	PDF	
OPEN ACCESS Development of C	Castor Oil as Local	Demulsifier to Overcome Water-Oil Emulsion	012013
	View article	► PDF	
OPEN ACCESS Aged Reduction P Pesanggaran Distr WN Wari, E Suryani	Prediction of the Ro rict, Banyuwangi i, Y Ulfiyati and IW S	oad Plan Due to Overload On the Pancer Road, Syafa'at	012014
+ Open abstract	View article	PDF	
OPEN ACCESS			012015
Inhibition of Free C Light treatment	Fatty Acids genera	ation in Crude Palm Oil during storage by using UV-	
S D Said, T Maimun	n, T M Asnawi and A	Muslim	
	View article	🔁 PDF	
OPEN ACCESS	atad with Indium 7	Tin Oxida for Tomporatura Songar Application	012016
D-shape Floer Co.			
Hopen abstract	Abdul Knudus, E Ha	PDF	
OBEN ACCESS			01001-
A Laboratory Sca Tonis Wax ys Baradfin sqc.our Brivacy and	le Synthesis of Eth ic Bruda AilnMitig Cookies molicy	anol from Agricultural Waste as Bio-based Solvent set in site you agree to our use of cookies. To find out more,	012017

IOP Conference Series: Materials Science and Engineering, Volume 854, 2020 - IOPscience

	Tiew article	PDF	
OPEN ACCESS Generation of Q-s Based Saturable A	witched Erbium-Debsorber	oped Fiber Laser Using Titanium Dioxide Film	012018
N Ahmed, NH Kama	rulzaman, NF Zulkip	li, Z Jusoh, HA Rahman and SW Harun	
	Tiew article	🔁 PDF	
OPEN ACCESS Synthesis and Cha and Clay Mixture	racterization of Mi Using Sintering M	icrofiltration Ceramic Membrane Based on Fly Ash ethod	012019
S Diana, R Fauzan, N	N Arahman, F Razi an	nd E Elfiana	
	Tiew article	🔁 PDF	
OPEN ACCESS Waste Mud in Oil	and Gas CEPU PP	SDM Using Bioremediation	012020
Yanty Maryanty, Sig	it Hadiantoro, Anang	Takwanto, Kamilia and Linga Ardhanariswari	
	Tiew article	PDF	
OPEN ACCESS Passively Q-switch shaped Fiber as Sa	hed Erbium-doped turable Absorber	Fiber Laser using Tungsten Disulfide deposited D-	012021
S Omar, B Musa, Z J	usoh, MIM Alı, AAA	A Jafry and SW Harun	
	View article	PDF	
OPEN ACCESS Effect of H_2O_2 as Temperature	the Foaming Agen	t on the Geopolymer Mortar using Curing of Room	012022
Faisal Rizal, Ari Putr	ra Pratama, Khamista	n, Amir Fauzi, Syarwan and Ahyari Azka	
	Tiew article	PDF	
OPEN ACCESS Thermal Transpor Containing Metall	t Feasibility of (Wa ic Oxides: Mathem	ater + Ethylene Glycol)-Based Nanofluids natical Approach	012023
Omer A Alawi, A R	Mallah, S N Kazi, M	N M Zubir and C S Oon	
	Tiew article	🔁 PDF	
OPEN ACCESS Optimization Desi Weighted Principa	gn of Electrochem l Component Anal	ical Machining Process of SKD11 Tool Steel Using ysis (WPCA)	012024
N Lusi, D R Pamuji, This site uses cookie secoperPabsacactand (A Afandi and G S Pr s. By continuing to us Coakiðsigwlarticle	ayogo se this site you agree to our use of cookies. To find out more, PDF	0

OPEN ACCESS			012025
Development of	Web Based Real In	me Remote Laboratory for Teaching and Learning	
Faisal Mahmud, Mo	ohd Nashrul Mohd Zu	bir, Mohd Yazed Bin Ahmad, Zuraidah Binti Abdullah,	
Nahrızul Adıb Bın I	Kadrı, Unaızah Hanur	n Binti Obaidellah and Tousif Amin Faisal MD	
	View article	🔁 PDF	
OPEN ACCESS			012026
The Impact of Ar	nthropometry on Te	erasi Packaging	
Meri Andriani and I	Rita Syntia		
	View article	🔁 PDF	
OPEN ACCESS			012027
Increased Absorp Microwave Techn	otion Capacity Of C nology	Organokaolin Adsorbents In Absorb Metals Using	
Syafruddin, Alfian	Putra, Suci Ramadhan	a and Pardi	
	View article	PDF	
OPEN ACCESS			012028
Use of Software Limpok Bridge	Engineering on the	Project Implementation Schedule of Lamreung	
Abdul Muhyi, Mifta	ahul Hamzi and Busra		
	View article	🔁 PDF	
OPEN ACCESS			012029
Separation of Ole as Solvent	eoresin from Nutme	eg Using Ultrasound Assisted Extraction and Hexane	
Victoria Kristina Ar	naningsih, Bernadeta S	Soedarini and Emerentiana Karina	
	View article	PDF	
OPEN ACCESS			012030
Bioethanol Produ Fiber	ction from Alkali S	Steam Explosion of Oil Palm of Empty Fruit Bunch	
Yanni Sudiyani, Eka	a Tri Wahyuni, Murya	nto Muryanto, Sephtian Marno and Nelizza Putri	
	View article	🔁 PDF	
OPEN ACCESS			012031
Durability and Ta	aste of Tofu with "Ie	e Asam Sunti" Coagulant	
Salmyah, Fachrania	ıh, Fajri and Maulizar		
	Tiew article	🔁 PDF	
This site uses cooki	es. By continuing to u	se this site you agree to our use of cookies. To find out more,	
ore ionr Acivacy sund	Cookies policy.		012032

	f Wafer Originated	from Coffee Waste as Ruminant Animal Feed	
Milawarni, Arskadi	us, E. Elfiana and Yas	sir	
	View article	🔁 PDF	
OPEN ACCESS Window Cleaning	g Robot by using A	rduino as Microcontroller	(
Arni Munira Marko Zakiah Mohd Yusot	om, Muhammad Asyra ff	ffuddeen Bin Arriffinjee, Muhammad Fikri Bin Haironi and	
	View article	🔁 PDF	
OPEN ACCESS Lateral Control o Piezoelectric Lay	f Functionally Grac ver	led Composite Beam under Static Load by using	(
Abdolreza Toudehd	lehghan		
+ Open abstract	Tiew article	🔁 PDF	
The Shortest Path A F Pratiwi, S D Ri + Open abstract	n Finder for Tsunan iyanto, R Listyaningru View article	ni Evacuation Strategy using Dijkstra Algorithm m and G M Aji PDF	
Science			
Science OPEN ACCESS Static Analysis of Levy Method	f Functionally Grad	led Coated Plate on Elastic Foundation Based on	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd	f Functionally Grad	led Coated Plate on Elastic Foundation Based on	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd + Open abstract	f Functionally Grad lehghan I View article	led Coated Plate on Elastic Foundation Based on	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd + Open abstract OPEN ACCESS Microsecond Pul Region	f Functionally Grad lehghan	led Coated Plate on Elastic Foundation Based on PDF g Bismuth Salenide as Saturable Absorber in 1.5 μm	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd + Open abstract OPEN ACCESS Microsecond Pul Region R A M Yusoff, A A	f Functionally Grad lehghan	led Coated Plate on Elastic Foundation Based on PDF g Bismuth Salenide as Saturable Absorber in 1.5 μm , N Kasim, S N M Rifin, Y Munajat and S W Harun	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd + Open abstract OPEN ACCESS Microsecond Pul Region R A M Yusoff, A A + Open abstract	f Functionally Grad lehghan Tiew article se Generation using . A Jafry, N F Zulkipli	led Coated Plate on Elastic Foundation Based on PDF g Bismuth Salenide as Saturable Absorber in 1.5 μm , N Kasim, S N M Rifin, Y Munajat and S W Harun PDF	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd + Open abstract OPEN ACCESS Microsecond Pul Region R A M Yusoff, A A + Open abstract OPEN ACCESS Nanosecond Puls Lutetium Oxide	f Functionally Grad lehghan Tien View article se Generation using A Jafry, N F Zulkipli View article se Erbium-Doped Fi	led Coated Plate on Elastic Foundation Based on PDF g Bismuth Salenide as Saturable Absorber in 1.5 μm , N Kasim, S N M Rifin, Y Munajat and S W Harun PDF iber Laser based on Evanescent Field Interaction with	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd + Open abstract OPEN ACCESS Microsecond Pul Region R A M Yusoff, A A + Open abstract OPEN ACCESS Nanosecond Puls Lutetium Oxide A A A Jafry, R A M	f Functionally Grad lehghan Tiew article se Generation using A Jafry, N F Zulkipli View article se Erbium-Doped Final M Yusoff, N Kasim, S I	led Coated Plate on Elastic Foundation Based on	(
Science OPEN ACCESS Static Analysis of Levy Method Abdolreza Toudehd + Open abstract OPEN ACCESS Microsecond Pul Region R A M Yusoff, A A + Open abstract OPEN ACCESS Nanosecond Puls Lutetium Oxide A A A Jafry, R A M + Open abstract	f Functionally Grad lehghan Twiew article se Generation using A Jafry, N F Zulkipli View article se Erbium-Doped Final A Yusoff, N Kasim, S T View article	led Coated Plate on Elastic Foundation Based on PDF g Bismuth Salenide as Saturable Absorber in 1.5 μm , N Kasim, S N M Rifin, Y Munajat and S W Harun ▷ PDF iber Laser based on Evanescent Field Interaction with N M Rifin, A R Muhammad and S W Harun ▷ PDF	

,0			
OPEN ACCESS			012039
Pollutant Absorber	Design to Minim	ize Air Pollution Emissions from Industry	
Yayat Ruhiat and Yuc	li Guntara		
	View article	PDF	
OPEN ACCESS			012040
Geographic Inform City Governance	nation System for	Waste Management for the Development of Smart	
N Tri Suswanto Sapta	adi, Phie Chyan and	Andrew Christopher Pratama	
	View article	🔁 PDF	
OPEN ACCESS			012041
Pore Pressure Pred	liction using Anfis	Method on Well and Seismic Data Field "Ayah"	
D Andrian, M S Rosi	d and M R Septyand	y	
	View article	PDF	
OPEN ACCESS Characterization of Analysis	f Lombok Earthqu	akes on July-August 2018 using Focal Mechanism	012042
T Karima, S K Wijay	a, M S Rosid, S Roh	adi and Y H Perdana	
	View article	🔁 PDF	
OPEN ACCESS The Implementatic Literature Review	on of Augmented I	Reality in Increasing Student Motivation: Systematic	012043
Nur Farah Syuhada M	Iohamad Saadon, Ib	rahim Ahmad and Ahmad Naim Chee Pee @ Che Hanapi	
	View article	PDF	
OPEN ACCESS Identification the J Derivatives) Metho K N Yudyawati and M	akarta Fault using od Gravity Data ⁄I S Rosid	MS-SVD (Multi Scale - Second Vertical	012044
+ Open abstract	View article	PDF	
OPEN ACCESS Smart Bed Using V	/oice Recognition	for Paralyzed Patient	012045
Nurul Fadillah and A	hmad Ihsan		
+ Open abstract	View article	PDF	
OPEN ACCESS IntelligenteSystems see our Privacy and C N Novianda, F Liza a	o BActotinatics Shu Cookies policy. Ind I Ahmad	in the section of the	012046

+ Open abstract	View article	PDF	
OPEN ACCESS Effect of Addition PLA-Based Nano	n of Chitosan-ZnO composites for Bio	as an Antibacterial on The Thermal Stability of film Packaging	012047
T Rihayat, S Riskina	a, Nurhanifa and R Sy	rahyadi	
	View article	PDF	
OPEN ACCESS			012048
Preparation, Char Chitosan as A Sus Devices	acterization of Palr stainable Raw Mate	n Oil Based Polyols Reinforced with Bentonite- erial for Anti-Bacterial Polyurethane Coatings in Medica	al
T Rihayat, Nurhanif	à, S Riskina and Y Yı	inus	
	View article	PDF	
OPEN ACCESS Synthesis of Casto Nanocomposite P Equipment	or Oil-Based Polyo olyurethane Coatin	ls Reinforced with Organoclay-Chitosan as gs in The Application of Environmentally Friendly Med	012049 lical
T Rihayat, K Y Putr	i, Y Yunus and S Risk	sina	
+ Open abstract	View article	PDF	
 OPEN ACCESS Chitosan Modified Suryani, Fitria, T Ri + Open abstract 	d Bio-Fibre Based hayat, Nurhanifa and F View article	Board as Antimicrobial and Anti-Crack Board T Y R Hasnah PDF	012050
OPEN ACCESS Refining Citronel (Photovoltaics)	la Oil (Cymbopogo	on Nardus L) by Utilizing Sunlight Using Solar Cells	012051
N Safitri, R Syahput	rra, K Y Putri, T Riha	yat and Nurhanifa	
← Open abstract	View article	PDF	
OPEN ACCESS Detection of Emp Ahmad Ihsan, Nurul	ty Slots in Car Parl Fadillah, C R Gunaw	king System Using Neural Network Method van and Mursyidah Mursyidah	012052
+ Open abstract	View article	PDF	
OPEN ACCESS Fault Plane Estim Lombok Earthqua This site uses cookie M S Rosid, R Widya see our Privacy and	ation Through Hyp ikes Relocated by u es. By continuing to u arta, T. Karima, S.K. W Cookies policy.	oocentres Distribution of the July-August 2018 using Double Difference Method se this site you agree to our use of cookies. To find out more, /ijaya and S Rohadi	012053

	View article	PDF	
OPEN ACCESS			012054
Identification of I Tomography Lon	Fault Structure in Landon Fault Structure in Landon Farthquake Date (1997)	ombok region, West Nusa Tenggara using ata of July-August 2018	012004
R Widyarta, S K Wi	ijaya, M S Rosid and S	S Rohadi	
	View article	PDF	
OPEN ACCESS			012055
Structure identifie	cation of geotherma	al field "X" using ML-SVD method of gravity data	
M A Naufal and M	S Rosid		
	Tiew article	PDF	
OPEN ACCESS	Potontial Distributio	on of Gold Mineralization Zone of High Sulfidation	012056
Epithermal Syster Mountain Qrea	m using Time-Dom	ain Induced Polarization (TDIP) and Magnetic Method	l at "N"
M F Khoir and M S	Rosid		
+ Open abstract	Tiew article	🔁 PDF	
OPEN ACCESS			012057
Performance Ana Parallelizing Spar	llysis of CUDA by rse Matrix-Vector M	Implementation of Hypergraph Partitioning for Iultiplication Using Quadro K4200	
Murni and T Handh	ika		
+ Open abstract	View article	🔁 PDF	
OPEN ACCESS			012058
Ultrasound Assis Bleaching Earth a	ted the Degradation as a catalyst	of Methylene Blue Using WO3-Deoiled Spent	
Noor Hindryawati, I	R.R. Dirgarini Julia N	.S, Aman S. Panggabean and Wilsoma	
+ Open abstract	View article	PDF	
OPEN ACCESS			012059
Q-switched Erbiu a Saturable Absor	ım-Doped Fiber Las rber	ser Incorporating Multi-Walled Carbon Nanotubes as	
C Huda, M Yasin, S	SW Harun, A A A Jafr	y and A H A Rosol	
	Tiew article	PDF	
OPEN ACCESS			012060
The simulation of	t evacuation from m	nultistorey building using NetLogo	
D.P. Lestari, A. Sabr This site uses cooking CopenPartsaca, and	i, T. Handhika, Murni, es. By continuing to us Coakits:polarticle	I Sari and A Fahrurozi se this site you agree to our use of cookies. To find out more, PDF	Ø

OPEN ACCESS Travel Time Estin	mation for Destinat	ion In Bali Using kNN-Regression Method with	012061
lensorflow			
Murni, R Kosasih, A	A Fahrurozi, T Handh	ika, I Sari and D P Lestari	
	View article	🔁 PDF	
OPEN ACCESS			012062
A Study on Nitrie	ding Alloy Steel in	INTI Plasma Focus Machine	
A Singh, R Jeyagop	oi, T O Teh, S Manme	shpal, S H Saw and S Lee	
	View article	🔁 PDF	
OPEN ACCESS			012063
Reservoir Charac Method on "Esse	eterization with Acc n" Field, Talang Ak	oustic Impedance Inversion and Multi attribute kar Formation, Sub-Ciputat Basin, North West Java	
E S Nugroho, A Riy	yanto and M Suardana	L Contraction of the second	
	View article	🔁 PDF	
OPEN ACCESS Thermal Conduct	tivity of Some Mar	ble Stones Available in South Aceh District	012064
L Lindawati, N F Y	uliza and I Irwansyah		
	View article	PDF	
OPEN ACCESS Study of Dynami Power Stabilizer	c Stability Analysis System as Compen	s in the Sigura-gura Hydro Power Plant using the sation	012065
Zulfikar	_		
	View article	🔁 PDF	
OPEN ACCESS			012066
Analysis of the E Network Services	Effect of Frame Vari s on the Local Netw	ations on Improving the Quality of Streaming vork	
Atthariq, Mursydah	and Azhar		
	View article	🔁 PDF	
OPEN ACCESS Mapping of bases gravity data	ment layer in field '	'X" petroleum system using ESA – MWT technique	012067
M S Rosid and J Ar	ndrian		
	View article	🔁 PDF	
This site uses cooki SEE Shr Privaes Sand	es. By continuing to u Cookies policy.	se this site you agree to our use of cookies. To find out more,	012000

2, 2:25 PM	IOP Conference	ce Series: Materials Science and Engineering, Volume 854, 2020 - IOPscien	ice
Interaction of En	zyme-Substrate from	n Indigenous Cellulolytic Bacteria by Bioinformatics	
Yanty Maryanty, Tr	i adryati, Suharjono ar	nd Sutiman Bambang Sumitro	
	View article	PDF	
OPEN ACCESS			0
The Effectiveness Takengon, Centra	s of Coffee Bean Pr al Aceh	ocessing Machines in the Rezeki Farmers Group in	
Amri, Salahuddin a	nd Muhammad Rizka		
	View article	PDF	
OPEN ACCESS			0
Smart Power Mar	nagement System fo	or Ambulance	
Fauziah Che Mat, S	hah Erawati Binti Mo	khtar, Mohamad Badrol Hisyam and Sulaiman Wadi Harun	
	Tiew article	PDF	
OPEN ACCESS			0
Fibre-based Satur	rable Absorbers for	Pulsed Generations in the 1-micron Region	
M F A Rahman, M	T Ahmad, M F M Rus	di, A A Latiff and S W Harun	
	View article	PDF	
OPEN ACCESS	use of Rooffile RI	PV System Implementation: Materials and	0
Constructions		v System implementation. Materials and	
Nelly Safitri, Rizal	Syahyadi, Faisal Rizal	and Yassir	
+ Open abstract	View article	PDF	
OPEN ACCESS			0
Soot Formation M Comparison Stud	Model Performance ly	in Turbulent Non-Premix Ethylene Flame: A	
E Elwina, N Sylvia,	, W Wusnah, Y Yunaro	di and Y Bindar	
	Tiew article	PDF	
OPEN ACCESS			0
Effect of the Seed	ding Thickness on t	he Growth of ZnO Nanorods prepared by CBD	
N Rosli, M M Halir	n, M R Hashim, W Ma	aryam, M F M Rusdi and A R Muhammad	
	Tiew article	PDF	
			0
OPEN ACCESS			
OPEN ACCESS Microbottle-Resc	onator Ethanol Liqu	id Sensor	

 Open abstract 	View article	🔁 PDF
-----------------------------------	--------------	-------

OPEN ACCESS			012076
Formulating an <i>A</i> as Filter Media fo	Anorganic Membran or Peat Water Purifi	e Using Clay, Activated Carbon and Micro Zeolite cation	
N Nahar, S Saifudd	in and Muhammad Sa	mi	
	View article	🔁 PDF	
Journal home			
JOURNAL LINK	XS		
Journal scope			
Information for org	anizers		
Information for aut	hors		
Contact us			
Reprint services fro	om Curran Associates		



This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.



This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.

8



IOP Conference Series: Materials Science and Engineering

Table of contents

Volume 854

2020

Previous issue
Next issue >

THE 2ND INTERNATIONAL CONFERENCE ON SCIENCE AND INNOVATED ENGINEERING 9 - 10 November 2019, Malacca, Malaysia

Accepted papers received: 28 April 2020 Published online: 01 July 2020

Editorial Board

Editor-in-Chief

Andreas Buchleitner Albert Ludwigs University Freiburg, Germany

Executive Editorial Board

Andrea Alu City University of New York, USA

Qiang Zhang University of Science and Technology of China, Shanghai, China

Editorial Board

Janet Anders University of Exeter, UK

Elke Arenholz Cornell High Energy Synchrotron Source (CHESS), USA

Joonwoo Bae Korea Advanced Institute of Science and Technology (KAIST), South Korea

Mari Carmen Banuls Max Planck Institute for Quantum Optics, Germany

Thomas Blackburn University of Gothenburg, Sweden

Jordi Boronat Universitat Politècnica de Catalunya, BarcelonaTech, Spain

Johan Chang University of Zurich, Switzerland

Lauriane Chomaz Heidelberg University, Germany

Christophe Couteau University of Technology of Troyes, France

Alexandre Dauphin The Institute of Photonic Sciences (ICFO), Spain

Franklin Dollar University of California Irvine, USA

Ora Entin-Wohlman Tel Aviv University, Israel

Rosario Fazio Scuola Normale di Pisa, Italy

Romain Fleury Ecole polytechnique f?d?rale de Lausanne, Switzerland

Alejandro González-Tudela IFF, CSIC, Madrid, Spain

Gregory Grason University of Massachusetts Amherst, USA

Jiandong Guo Institute of Physics, Chinese Academy of Sciences, China

Philipp Höhn Okinawa Institute of Science and Technology, Japan

Plamen Ch. Ivanov Boston University and Harvard Medical School, USA

Shirngite Katsumbtes. To find out more, see our Privacy and Cookies policy.

Ξ

Sarah Köster Georg-August-University Göttingen, Germany Alexandra Landsman Ohio State University, USA Tim Langen Stuttgart University, Germany Chengcheng Liu Beijing Institute of Technology, China Andrea Macchi Istituto Nazionale di Ottica, Italy Stuart Mangles Imperial College London, UK Julia Mikhailova Princeton University Yamir Moreno University of Zaragoza, Spain Takahiro Moriyama Kyoto University, Japan Rosario Nunzio Mantegna University of Palermo, Italy Silke Ospelkaus Leibniz Universität Hannover, Germany Mauro Paternostro Queen's University Belfast, Ireland Matjaž Perc University of Maribor, Slovenia Emanuele Poli Max Planck Institute for Plasma Physics, Germany Mingpu Qin Shanghai Jiao Tong University, China Vicent Romero-García Université du Maine, France Keiji Saito Keio University, Japan Piet Schmidt Physikalisch-Technische Bundesanstalt and Leibniz University Hannover, Germany Urbasi Sinha Raman Research Institute, India Thomas Speck Johannes Gutenberg-Universität Mainz, Germany Tobias Stauber ICMM, CSIC, Madrid, Spain Birgit Stiller Max Planck Institute for the Science of Light, Germany Mariam Tórtola University of Valencia, Spain Stefan Ulmer Institute of Physical and Chemical Research (Riken), Japan Karl Unterrainer Vienna University of Technology, Austria Patrizia Vignolo University of Nice - Sophia Antipolis, France Matchias sacios hipsi By snati Buys tuths Chisrite you agree to our use of cookies. To find out more,

see our Privacy and Cookies policy.

3

Claudia Wulz Institute of High Energy Physics of the Austrian Academy of Sciences, Austria

Hongjun Xiang Fudan University, China

Feihu Xu University of Science and Technology of China, China

Haitao Xu Tsinghua University, China

Andre Xuereb University of Malta, Malta

Yiqi Zhang Institute of Physics, Chinese Academy of Sciences, China

Xiao Zheng University of Science and Technology of China, China

Falko Ziebert Heidelberg University, Germany

JOURNAL LINKS

Submit an article		
About the journal		
Editorial Board		
Author guidelines	 	
Review for this journal	 	
Publication charges	 	
News and editorial	 	
Awards		
Journal collections		
~		

Contact us

This site uses cookies. By continuing to use this site you agree to our use of cookies. To find out more, see our Privacy and Cookies policy.

https://iopscience.iop.org/journal/1367-2630/page/Editorial Board Members

 $oldsymbol{\Theta}$

PAPER • OPEN ACCESS

A Laboratory Scale Synthesis of Ethanol from Agricultural Waste as Bio-based Solvent for Waxy-Paraffinic Crude Oil Mitigation

To cite this article: M K Afdhol et al 2020 IOP Conf. Ser.: Mater. Sci. Eng. 854 012017

View the article online for updates and enhancements.

You may also like

- <u>Characterization of compositions in crude</u> <u>oil and the effect of inhibitor on the</u> <u>crystallization of paraffin</u> Sen Peng, Xiaoben Tang, Anguo Yang et al.
- Experimental Study on Melting and Solidification of Phase Change Material Thermal Storage H Ambarita, I Abdullah, C A Siregar et al.
- <u>Wax inhibitor based on ethylene vinyl</u> acetate with methyl methacrylate and <u>diethanolamine for crude oil pipeline</u> S M Anisuzzaman, S Abang, A Bono et al.



This content was downloaded from IP address 223.130.23.100 on 27/01/2022 at 06:31

A Laboratory Scale Synthesis of Ethanol from Agricultural Waste as Bio-based Solvent for Waxy-Paraffinic Crude Oil Mitigation

M K Afdhol, Hidayat F, M Abdurrahman, U Z Husna, N P Sari, R K Wijaya

Department of Petroleum Engineering, Faculty of Engineering, Universitas Islam Riau. Jl. Kaharuddin *Nasution No.113 Km. 11, Pekanbaru, Riau – 28284, Indonesia*.

Email: Afdhol@eng.uir.ac.id

Abstract. Paraffin is a problem commonly faced in petroleum production. The presence of paraffin can inhibit the process of oil flow. Mitigation methods commonly used to overcome this problem is by using chemical injection, which is solvent. In this research, a laboratory experiment was conducted to make bioethanol from agricultural waste that are rice husks and corn cobs. This bioethanol functions as a solvent that is used to reduce the pour point in a waxy-paraffinic crude oil sample. Oil samples were mixed with bioethanol with different mixing ratios, including 5%, 10%, 15%, 20% 50%. The results showed that the alcohol content of the Husk and Corncob rise was 11% and 9% respectively. Then, the best result from mixing of bioethanol with oil reduced the pour point from 43.3 to 41 at mixing ratio of 50%.

1. Introduction

1.1. Wax Paraffin

The problem of paraffin wax is a very crucial problem in the oil field because it can cause oil to not flow when the temperature is below the pouring point (Abdurrahman, Ferizal, Husna, & Pangaribuan, 2018). Paraffin wax is part of hydrocarbons, which cannot be dissolved by crude oil under normal conditions, where the normal conditions of crude oil that have been tested are at a temperature of 70-150 °C and at a pressure of 55-103 Mpa (Wang, Wu, Creek, Shuler, & Tang, 2003).

There are several methods to overcome paraffin wax, one of which is the preventive method of heating and using chemicals, one of the most effective methods is using a hydrocarbon solvent (Afdhol, Lubis, & Siregar, 2019; Khaibullina, 2016). According to Al-yaari & Fahd (2011) for examples of injection schemes using solvents can be seen in Figure 1. The solvent injection device proposed by C-FER Technologies.

IOP Conf. Series: Materials Science and Engineering

854 (2020) 012017 d

doi:10.1088/1757-899X/854/1/012017



Figure 1. Wax (Huang, Wang, Li, Ren, & Zhu, 2017)

1.2. Bioethanol Production

Ethanol is produced through several processes, namely hydrolysis and fermentation using food ingredients that contain starch carbohydrates, such as rice and tubers (Cai, Liu, He, Chai, & Cai, 2018). Biomass containing lignocellulose can be used as a source of reducing sugars such as glucose, xylose and maltose (Mahboubi et al., 2017). In the next step, the alcohol produced must be turned into steam through a distillation process with a temperature of 78.5°C (Salehi, Taghizadeh-alisaraei, Shahidi, & Jahanbakhshi, 2018). According to (Cai et al., 2018) several stages of the biomass process will be carried out to produce ethanol, namely pretreatment, hydrolysis and fermentation. Biomass pretreatment is important because it is to get high ethanol yield. The purpose of pretreatment is to break the structure of lignocellulose so that cellulose is separated from lignin and thus cellulose. Hydrolysis is the process of breaking down polysaccharides in lignocellulosic biomass, which are cellulose and hemicellulose which will be broken down into sugar monomers. Perfect cellulose hydrolysis will produce glucose. Hydrolysis can be done chemically using acids or enzymatically. There are several factors that influence the hydrolysis process, namely carbohydrate content of raw materials, pH of hydrolysis, hydrolysis time, temperature and pressure. Fermentation is microbial activity in food so that the desired product is produced. Common microbes involved in fermentation are bacteria, yeast and mold.

There are important factors that will affect ethanol yield and efficiency. First, under physiological conditions the microbes are added to the media, which depends on the optimal optimum growth conditions of the microbes to be used. Second, the environmental conditions during the fermentation, i.e. pH and temperature. Bioethanol raw materials can be derived from cellulose source materials such as rice straw, bagasse, corncobs and rice husks (Said, Wahid, Diah, & Sabang, 2014). Utilization of biomass has been done a lot such as oil palm shells (Yuliusman, Nasruddin, Afdhol, Amiliana, et al., 2017), coffee grounds and others(Yuliusman, Nasruddin, Afdhol, Haris, et al., 2017). The production of bioethanol from cellulose waste has been developed, rice husk is one of the renewable raw materials used for making bioethanol as it is easily available and very economical (Kouteu Nanssou, Jiokap Nono, & Kapseu, 2016).

1.2.1. Rice Husk

Rice husk (Figure 2) contains several organic compounds namely, lignin, cellulose, hemicellulose, nitrogen compounds, vitamin B and organic acids and contains inorganic compounds in the form of silica (Ebrahimi, Caparanga, Ordono, Villaflores, & Pouriman, 2017). Rice Husk (RH), a broad covering of rice grain which accounts for around 20% of rice, has the potential to produce about 0.4 sugar per 1 gram of dry RH and the sugar process can further be fermented into bioethanol (Ebrahimi et al., 2017).

IOP Conf. Series: Materials Science and Engineering

854 (2020) 012017

doi:10.1088/1757-899X/854/1/012017



Figure 2. Rice husks (Cai et al., 2018)

Table 1. Composition of Rice Husks					
Component	Rice Husks	Rice Bran	Broken Rice		
starch	6.9	28.5	68.6		
Cellulose	38.4	4.6	1.8		
Ash	15.9	8.0	1.5		
Hemicellulose	16.1	8.4	3.7		
Lignin	16.7	2.8	-		
Protein	3.4	12.9	9.9		
Sources (Emerge at a^{1} 2017)					

Source : (Favaro et al., 2017)

It can be seen in Table 1 that the cellulose and hemicellulose content in rice husk is the largest at 38.4% and 16.1% so that it can be used as a source of bioethanol production.

1.2.2. Corn Cobs

In corn plants consist of corn kelobot, corn hair, corn cobs and corn kernels. Corn plants based on systematics (taxonomy) of plants are classified as follows (Sain, 2016).

Table 2. Taxonomic sta	Table 2. Taxonomic status of maize (Sain, 2016)		
Regnum	Plantae		
Devisio	Spermatophyte		
Sub Devisio	Angiospermae		
Classis	Monocotyphyta		
Ordo	Graminae		
Familia	Graminaceae		
Genus	Zea		
Species	Zea mays L.		

Corn contains crude fiber which is composed of complex compounds of lignin, hemicellulose and cellulose (lignocellulose), and each one is a compound that can potentially be converted into other compounds biologically. The dry solid content of Corncob by using alkaline, solvent or ammonia based pretreatments produces the greatest amount of ethanol (19-22%), whereas mushroom based pretreatments produce much less (11%) (Zhao, Damgaard, & Christensen, 2018).



Figure 3. Corncob waste (Fachry, Astuti, & Puspitasari, 2013)

The complex compounds of lignin, hemicellulose and cellulose (lignocellulose) each are compounds that can potentially be converted into other compounds biologically and the following table compositions of these compounds from several materials:

Table 3. Composition of Cellulose,	Hemicellulose and Lignin free	om different Lignocellulose (Byadgi
	& Kalburgi, 2016)		

Lignocellulosic Material	Cellulose (%)	Hemicellulose (%)	Lignin (%)
Miscanthus	40	18	25
Coastal Grass	25	35.7	9-18
Corncob	35-40	17-35	7-18
Wheat Straw	30	50	15

From the table above it can be seen that corn is a plant-based material with a compound that is easily converted into alcohol, so this study takes corn as a raw material for making bio-ethanol solvents.

2. Material and Methods



Figure 4. Research's Fishbone

2.1. Raw Materials

Materials used in this study comprises of rice husks, corncobs, acetic acid, chloric acid, sulfuric acid, NaOH, saccharomyces and distilled water.

2.2. Hydrolysis

Prepare materials that are ready for hydrolysis with sizes 30, 50, 80, 100 and 200 mesh. Enter the ingredients as much as 15 grams into a beaker (Hayuningtyas, Sk, & Sla, 2014). Then add a solution of sulfuric acid and hydrochloric acid as much as 150 ml each with a temperature of 100°C for 2.5-3 hours (Hayuningtyas et al., 2014) at 5% acid concentration. Repeat steps 2 and 3 for acid concentrations of 10%, 15% and 25%. The rice husk from hydrolysis is then filtered, where the hydrolyzed solution is the main product for the fermentation process (Osvaldo, S, & Faizal, 2012)

2.3. Fermentation

The rice husk hydrolysis substrate was ready to be fermented. Prepare anaerobic bacteria, the bacteria used are Saccharomyces Cerevisiae with pH conditions 3-4 (Azizah, N., Al-Baarri, A.N., dan Mulyani, 2012). Entering the results of hydrolysis of rice husk into the fermentation series that has been prepared. Add bread yeast (Utami & Windiyati, 2014) with a mass of 1.5 grams (Jayanti, 2011). Fermented for 5 days at 30°C. (Azizah, N., Al-Baarri, A.N., dan Mulyani, 2012)



Figure 5. Fermentation Process

2.4. Distillation (ASTM D1160)

The process of distillation (purification) is the stage of separating a substance based on its boiling point. The following stages of distillation: Take a sample of the fermentation that has been done. Weigh flash containing sample + thermometer. Clean and dry the measuring cup, place the measuring cup so that the tip of the outlet goes into the measuring cup of the distillate. Close the measuring cup to prevent the steam from coming out of the tube. Circulate coolant through the condenser. Run to warm up and adjust the temperature slowly so that the distillation liquid drips properly. Stop heating at the end boiling point and allow the distillate liquid to drip on the measuring cup. After cooling, record the volume of the distillate produced.

IOP Conf. Series: Materials Science and Engineering

854 (2020) 012017

doi:10.1088/1757-899X/854/1/012017



Figure 6. Distillation Tool Series

3. Calculation

3.1. Paraffin Wax Measurement

In this study using crude oil samples taken from field X and the following is the oil properties data in the field:

Table 4. 1 v 1 data and crude on properties in field X			
Information	Value	Unit	
Oil density	30,8	API	
Specific Gravity	0,8713	-	
Water phase density	1,00028	gr/cm ³	
Oil Viscosity	14,4	cp	
Water Viscosity	0,5	cp	
Pour Point	100	°F	
Flash Point	170	°F	
Reservoir Temperature	136	°F	
Bottom Hole Pressure	200-400	psig	
Reservoir Pressure	532	psig	
Bubble Point Pressure	113	psig	
Oil formation volume factor	1,049	-	
Initial Oil Saturation	63,1	%	
Depth Formation	1100-1200	ft	

Table 4. PVT data and crude oil properties in field X

Reservoir fluid composition is also one important parameter that needs to be known in order to be able to choose the type of solvent used and also to predict the formation of paraffin wax. The following is a table of reservoir fluid composition in field X:

Table 5. Composition of fluids in field X			
Component	Percent of Mol	Percent Weight	
Hydrogen sulphide	0,00	0,00	
Carbon dioxide	0,56	0,08	
Nitrogen	0,00	0,00	
Methane	0,67	0,04	
Ethane	0,67	0,07	
Propane	1,51	0,22	
Iso-Butane	0,90	0,18	
n-Butane	1,57	0,31	
Iso-Pentane	1,56	0,38	
n-Pentane	1,50	0,36	
Hexane	0,35	0,10	
Heptane Plus	90,71	98,26	
Total	100.00	100,00	

The data above becomes a reference for laboratory experiments conducted to find out indications of paraffin wax formation by the methods / tests carried out as described below referred to ASTM D97; Pour the sample into a tube of 10 cc. Insert the tube in the oven and heat it to the test temperature. Remove the tube containing the sample from the oven while the sample is still hot. Observe temperature changes when all samples can be poured

4. Results and Discussion

4.1. Sugar Reduction



Figure 7. Results of Reducing Sugar Based on Mesh Size Differences

Analysis of the results of reducing sugars on different mesh sizes such as Figure 7 rice husk shows that the smaller the size of the mesh used, the resulting reducing sugars are getting bigger. It was proven that when the 30 mesh size produced reducing sugar 9.17, the mesh size 50 produced the reducing sugar 10.29, the mesh size 80 produced the reducing sugar 11.32, the mesh size 100 produced the reducing sugar 11.92 and the mesh size 200 produced the reducing sugar by 13.8. so it can be concluded that the smaller the mesh used it will produce a large reducing sugar.

Figure 7 corncob shows that the higher the mesh size (the finer) the reducing sugar content will be even higher while the size of 80 mesh will decrease because it can be caused by several factors such as errors during hydrolysis and the sample when tested experiencing changes in properties and after testing as much as 2 times the researcher regards it as an anomaly in the study because viewed from the trendline has shown a graph that increases with the mesh size.

THE 2ND INTERNATIONAL CONFERENCE ON S	CIENCE AND INNOVATE	D ENGINEERING	IOP Publishing
IOP Conf. Series: Materials Science and Engineering	854 (2020) 012017	doi:10.1088/1757	-899X/854/1/012017

According to Osvaldo et al., (2012) the size of the raw material used will affect the size of the porosity so that it can maximize contact between the material and the acid to increase the results of cellulose hydrolysis so that the smaller the size of the material used, the greater the yield of reduced sugar.



Figure 8. Results of Reducing Sugar Based on Differences in Acid Concentration

Meanwhile, for the observation of Figure 8 rice husk regarding the results of reducing sugars which is influenced by different acid concentrations, it is known that the higher the concentration of sulfuric acid used in the hydrolysis process, the results of the reducing sugars are also greater. Can be seen in the picture when the 5% acid concentration results in reducing sugar by 0.7, 10% acid concentration produces 7.72% reducing sugar, 15% acid concentration produces 8.9% reducing sugar, 20% concentration produces 10.04 reducing sugar and 25% concentration produces reducing sugar equal to 11.17.

From Figure 8 it can be seen that the higher the concentration of acid used, the higher the level of reducing sugar. The higher the reducing sugar levels, the more ethanol will be produced. the highest acid concentration is 20% HCL and also the advantage of using strong acids at low concentrations is that there is no need for acid recovery and the absence of acid ions lost in the process.

4.2. Alcohol Product from Fermentation



Figure 9. Distillation Circuit

In Figure 9 shows the entire distillation circuit consisting of a core series of sample containers, heaters, thermometers and measuring cups for the distillate reservoir. The boiling point of alcohol is around 78°C (Fachry et al., 2013; Jaya, Arthawan, & Sari, 2012; Salehi et al., 2018). Then the temperature in the distillation device is set to 78°C so that the resulting distillate is a type of bioethanol alcohol. The percentage of alcohol in the rice husk distillate sample is 8%. In previous studies using rice husk fermented for 5 days produced alcohol by 14.4227% (Utami & Windiyati, 2014)

The bioethanol that has been made is measured by using alcohol meter alcohol meter and after measuring the alcohol content obtained from bioethanol from corncob waste by 11% where this is a fairly high alcohol content which based on research that has been done before the dry solid content of Corncob produce the greatest amount of ethanol (19-22%) (Zhao et al., 2018).

4.3. Alcohol Characterization of Synthetic Solvent and Bio-Solvent

Table 6. Characteristics of synthetic solvents and bioethanol			
Duanautias	Bioethanol		Davagel II
Properties	Rice Husk	Corn Cob	
Density, gr/cc	0.971	0,984	0.8528
SG	0.971	0,984	0.8528
°API	14.13	12.30	34.42
Color	Colorless	Colorless	Colorless
Odor	Aromatic	Aromatic	Aromatic
pН	4	4	9
Viscosity, cp	0.752	0.80	-
Flash Point, °C	48	45	16.1
<i>Fire Point</i> , °C	54	56	-

The advantage of bioethanol from agricultural waste is the value of the sample flash point where the rice husk flash point is 48°C, which means that at room temperature the sample has not been burned so it is safe to use on a laboratory scale. This is the advantage of bioethanol over parasol II, because parasol II has a flash point 16.1 which means below room temperature that is 30°C parasol II will be flammable so bioethanol is more safety than parasol II.

Bioethanol from corncob based on flash point and fire point testing can be said to be more safety for the application of production wells and production pipes, with a flash point of 45° C and a fire point of 56° C. This can be indicated that the bioethanol produced is non-flammable compared to synthetic solvents.

4.4. Paraffin Wax Test Results

Tests carried out to identify the success of solvents in overcoming the problem of paraffin wax in oil, namely testing the pour point (ASTM D97). In this test, two tests were conducted, namely testing the pouring point of oil before mixing the solvent and the pouring point of oil after mixing the solvent. The following table shows the results of tests conducted on three oil samples.

Table 7. Testing of Pour Oil Before Mixing Solvent					
Simple Name	Pour Point	Unit			
LGK (11-07-2018)	44	°C			
LGK (24-04-2018)	43	°C			
LGK (28-06-2018)	43	°C			
Average	43,3	°C			

In the results table above is the initial pour point temperature of oil containing paraffin wax before the solvent is mixed. Furthermore, to test the feasibility of the solvent from the corncob material that has been made, the solvent is mixed with the oil sample above with the amount of oil sample of 10 ml with a percentage of many solvents added namely 5%, 10%, 15%, 20%, 50% and 100% so we get the test results as in the table below:

Table 6. Testing of the Total Tohit of Oh After Solvent Wixing							
Sample Name	Pour Point						
	5%	10%	15%	20%	50%	100%	
Sample I	44°C	44°C	44°C	43°C	42°C	41°C	
Sample II	43°C	43°C	42°C	42°C	41°C	40°C	
Sample III	43°C	42°C	42°C	41°C	40°C	39°C	
Average	43,3°C	43°C	42,7°C	42°C	41°C	40°C	

Table 8. Testing of the Pour Point of Oil After Solvent Mixing



Figure 10. Pour Point Testing After being mixed with Solvent

Seen from the table and figure above, it can be seen that there is a change in value at the pouring point test before and after the solvent is mixed. Changes in the temperature of the pouring point of this oil can indicate the effect of mixing the solvent on the oil containing paraffin wax where the oil in the sample is average with an initial temperature of 43.3°C which means that oil for the first time can flow and by mixing the solvent with the pouring temperature oil into 40°C which shows that after being mixed with oil solvent it is easier to flow at a lower temperature than the initial temperature of the oil so that this can overcome the problem of paraffin wax on oil where with paraffin wax the oil becomes more difficult to flow but with the addition the oil pour point solvent decreases and even at low temperatures the oil can still flow more easily than oil without mixing with the solvent.

5. Conclusion

Based on the results of the analysis in the manufacture of bioethanol and the application of bioethanol to oils with high paraffin levels, the following conclusions are obtained:

- 1. The characteristics of the bioethanol produced can be seen from the density, SG, viscosity, PH, aroma and physical form that is almost the same as synthetic solvents and corncob itself has a match as bioethanol raw material because it produces an alcohol content of 11% and a risk husk of 9%.
- 2. Parameters that affect the manufacture of bioethanol such as reducing sugar content, particle size, acid concentration and cellulose content where the highest corncob reducing sugar content is 28.61%, optimal particle size is 200 mesh, optimal acid concentration is 20% HCl and cellulose content is corncob by 30-40%.
- 3. The average pouring point test results before mixing bioethanol is 43.30C then the oil sample is mixed with bioethanol with a mixing ratio of 5%, 10%, 15%, 20%, and 50% of the sample weight

so that the point temperature has decreased pour at the highest mixing ratio 100% to 40 0 C or a difference of 3.3 0 C.

References

- [1] Abdurrahman, M., Ferizal, F. H., Husna, U. Z., & Pangaribuan, L. (2018). *Possibility of Wax Control Techniques in Indonesian Oil Fields*. In *AIP*. doi:10.1063/1.5028059
- [2] Afdhol, M. K., Lubis, H. Z., & Siregar, C. P. (2019). Bioethanol Production from Tea Waste as a Basic Ingredient in Renewable Energy Sources. *Journal of Earth Energy Engineering; Vol 8 No 1 (2019): APRIL*. doi:10.25299/jeee.2019.vol8(1).2602
- [3] Al-yaari, M., & Fahd, K. (2011). Paraffin Wax Deposition : Mitigation & Removal Techniques. SPE International Symposium on Oilfield Chemistry 155412. doi:10.2118/155412-MS
- [4] Azizah, N., Al-Baarri, A.N., dan Mulyani, S. (2012). Pengaruh Lama Fermentasi Terhadap Kadar Alkohol, pH, dan Produksi Gas pada Proses Fermentasi Bioetanol dari Whey dengan Substitusi Kulit Nanas. Jurnal Aplikasi Teknologi Pangan, 1(2), 72–77. doi:10.17728/JATP.V113.73
- [5] Byadgi, S. A., & Kalburgi, P. B. (2016). Production of Bioethanol from Waste Newspaper. *Procedia Environmental Sciences*, *35*, 555–562. doi:10.1016/j.proenv.2016.07.040
- [6] Cai, W., Liu, R., He, Y., Chai, M., & Cai, J. (2018). Bio-oil production from fast pyrolysis of rice husk in a commercial-scale plant with a downdraft circulating fluidized bed reactor. *Fuel Processing Technology*, 171(November 2017), 308–317. doi:10.1016/j.fuproc.2017.12.001
- [7] Ebrahimi, M., Caparanga, A. R., Ordono, E. E., Villaflores, O. B., & Pouriman, M. (2017). Effect of ammonium carbonate pretreatment on the enzymatic digestibility, structural characteristics of rice husk and bioethanol production via simultaneous saccharification and fermentation process with Saccharomyces cerevisiae Hansen 2055. *Industrial Crops and Products*, 101, 84–91. doi:10.1016/j.indcrop.2017.03.006
- [8] Fachry, A. R., Astuti, P., & Puspitasari, T. G. (2013). PEMBUATAN BIETANOL DARI LIMBAH TONGKOL JAGUNG DENGAN VARIASI KONSENTRASI ASAM KLORIDA DAN WAKTU FERMENTASI. Jurnal Teknik Kimia, 19(1), 60–69.
- [9] Favaro, L., Cagnin, L., Basaglia, M., Pizzocchero, V., van Zyl, W. H., & Casella, S. (2017). Production of bioethanol from multiple waste streams of rice milling. *Bioresource Technology*, 244(17), 151–159. doi:10.1016/j.biortech.2017.07.108
- [10] Hayuningtyas, S. R. I. K., Sk, H., & Sla, S. (2014). Produk bioetanol dari jerami padi (Oryza sativa) melalui hidrolisis asam dan fermentasi dengan Saccharomyces cerevisiae. Bioteknologi, 11(1), 1–4. doi:10.13057/biotek/c110101
- [11] Huang, Q., Wang, W., Li, W., Ren, Y., & Zhu, F. (2017). A pigging model for wax removal in pipes. In SPE Production and Operations (Vol. 32, pp. 469–475). doi:10.2118/181560-pa
- [12] Jaya, M. A. S., Arthawan, G. K. A., & Sari, A. N. (2012). Potensi nira kelapa sebagai bahan baku bioetanol. *Jurnal Bumi Lestari*, *12*(1), 85–92.
- [13] Jayanti, R. T. (2011). Pengaruh pH, suhu hidrolisis Enzim A-Amilase Dan Konsentrasi Ragi Roti Untuk Produksi Etanol Menggunakan Pati Bekatul.
- [14] Khaibullina, K. (2016). SPE-184502-STU Technology to Remove Asphaltene, Resin and Paraffin Deposits in Wells Using Organic Solvents.
- [15] Kouteu Nanssou, P. A., Jiokap Nono, Y., & Kapseu, C. (2016). Pretreatment of cassava stems and peelings by thermohydrolysis to enhance hydrolysis yield of cellulose in bioethanol production process. *Renewable Energy*, 97, 252–265. doi:10.1016/j.renene.2016.05.050
- [16] Mahboubi, A., Ylitervo, P., Doyen, W., De Wever, H., Molenberghs, B., & Taherzadeh, M. J. (2017). Continuous bioethanol fermentation from wheat straw hydrolysate with high suspended solid content using an immersed flat sheet membrane bioreactor. *Bioresource Technology*, 241(17), 296–308. doi:10.1016/j.biortech.2017.05.125
- [17] Osvaldo, Z. S., S. P. P., & Faizal, M. (2012). PENGARUH KONSENTRASI ASAM DAN WAKTU PADA PROSES HIDROLISIS DAN FERMENTASI PEMBUATAN

BIOETHANOL DARI ALANG-ALANG. Jurnal Teknik Kimia, 18(2), 52–62.

- [18] Said, M., Wahid, A., Diah, M., & Sabang, S. M. (2014). Sintesis Bioetnaol Dari Jerami Padi (Oryza Sativa L) Melalui Fermentasi. In ISSN 2302-6030 (pp. 178–182).
- [19] Sain, A. (2016). KERAGAMAN GENETIK EMPAT VARIETAS JAGUNG (Zea mays. L) BERSARI BEBAS MENGGUNAKAN MARKA SSRs (Simple Sequence Repeats).
- [20] Salehi, R., Taghizadeh-alisaraei, A., Shahidi, F., & Jahanbakhshi, A. (2018). Potentiometric of bioethanol production from cantaloupe waste (Magassi Neishabouri Cultivar). *Journal of the Saudi Society of Agricultural Sciences*. doi:10.1016/j.jssas.2018.05.006
- [21] Utami, I., & Windiyati, L. (2014). Pembuatan Bioetanol Dari Sekam Padi Menggunakan Kombinasi Soaking in Aqueous Ammonia (Saa) Pretreatment – Acid Pretreatment – Hidrolisis – Fermentasi, 20(1), 46–53.
- [22] Wang, K. S., Wu, C. H., Creek, J. L., Shuler, P. J., & Tang, Y. (2003). Evaluation of effects of selected wax inhibitors on paraffin deposition. In Petroleum Science and Technology (Vol. 21, pp. 369–379). doi:10.1081/LFT-120018526
- [23] Yuliusman, Nasruddin, Afdhol, M. K., Amiliana, R. A., Hanafi, A., & Rachmanda, B. (2017). Preparation of activated carbon from palm shells using KOH and ZnCl2 as the activating agent. In IOP Conference Series: Materials Science and Engineering (Vol. 180). doi:10.1088/1757-899X/180/1/012282
- [24] Yuliusman, Nasruddin, Afdhol, M. K., Haris, F., Amiliana, R. A., Hanafi, A., & Ramadhan, I. T. (2017). Production of activated carbon from coffee grounds using chemical and physical activation method. *Advanced Science Letters*, 23(6). doi:10.1166/asl.2017.8822
- [25] Zhao, Y., Damgaard, A., & Christensen, T. H. (2018). Bioethanol from corn stover À a review and technical assessment of alternative biotechnologies. *Progress in Energy and Combustion Science*, 67, 275–291. doi:10.1016/j.pecs.2018.03.004

