

PDF downloads: 37

THE ADSORPTION OF HEAVY METALS FROM INDUSTRIAL WASTEWATER USING SARGASSUM CRASSIFOLIUM

Lily Surayya	Eka	Putri,	Eka	Syafiqa
--------------	-----	--------	-----	---------

₽ 21-27

ß	pdf	

Abstract View : 28

Abstract View : 53

pdf downloads: 96

EFFECTS OF WATERSHED TOPOGRAPHY AND LAND USE ON BASEFLOW HYDROLOGY IN UPSTREAM KOMERING SOUTH SUMATERA, INDONESIA

Rosmalinda Permatasari, Arwin Sabar, Dantje Kardana Natakusumah, 📄 28-33 Hazairin Samaulah



Abstract View : 79

PDF downloads: 68

DATABASE STRUCTURE OF LAND ALLOCATION MANAGEMENT INFORMATION SYSTEM FOR ESTIMATING RUN-OFF IN

WATERSHEDS

Sarino, Dinar Dwi Anugerah Putranto, Agus Lestari Yuono, Imroatul Chalimah 🗎 34-42 Juliana



PDF downloads: 26

IMPROVEMENT OF PUBLIC TRANSPORT TO MINIMIZE AIR POLLUTION IN URBAN SPRAWL

Lasmini Ambarwati, Amelia K. Indriastuti 📄 43-50

PERFORMANCE OF A CIRCULATION TYPE PURIFICATION SYSTEM DURING THE TREATMENT OF SLUDGE FROM MANILA BAY AND TWO PORTS IN JAPAN

Komoriya Tomoe, Okamoto Kyoichi2, Toyama Takeshi, Hirano Hirosuke, 📄 51-56 Garcia Teodinis, Baccay Melito, Macasilhig Marjun, Fortaleza Benedicto

🔁 pdf	
Abstract View : 34	pdf downloads: 35
SETTLEMENT BEHAVIOR OF ROAD SURFACES CAUSED	ВҮ
Pongsagorn Poungchompu, Siwadol Saenseela, Gomin Chairatanangamdo	ej 🗎 57-61
Abstract View : 40	pdf downloads: 13
NFLUENCE OF DENSITY AND THICKNESS ON POLYSTY NSULATED CONCRETE BLOCK WALLS	RENE
Muawia Dafalla , Mohammed Al Shuraim , Abdullah Shaker	₿ 62-67
Abstract View : 45	pdf downloads: 37
ENVIRONMENTAL PARAMETERS CONTROLLING THE HA	BITAT OF ENTIFIED
ENVIRONMENTAL PARAMETERS CONTROLLING THE HA THE BRACKISH WATER CLAM CORBICULA JAPONICA ID BY PREDICTIVE MODELLING 'ukari Sugiyama , Mikio Nakamura , Suguru Senda, Michiko Masuda	BITAT OF ENTIFIED E 68-73
ENVIRONMENTAL PARAMETERS CONTROLLING THE HA THE BRACKISH WATER CLAM CORBICULA JAPONICA ID BY PREDICTIVE MODELLING ukari Sugiyama , Mikio Nakamura , Suguru Senda, Michiko Masuda De pdf Abstract View : 42	BITAT OF ENTIFIED 68-73 pdf downloads: 19
ENVIRONMENTAL PARAMETERS CONTROLLING THE HA THE BRACKISH WATER CLAM CORBICULA JAPONICA ID BY PREDICTIVE MODELLING (ukari Sugiyama , Mikio Nakamura , Suguru Senda, Michiko Masuda () pdf Abstract View : 42 STUDY ON STRENGTH ESTIMATION OF SOIL CEMENT U EMBEDDED PILE METHOD BY ELECTRICAL RESISTIVITY MEASUREMENT	BITAT OF ENTIFIED
ENVIRONMENTAL PARAMETERS CONTROLLING THE HA THE BRACKISH WATER CLAM CORBICULA JAPONICA ID BY PREDICTIVE MODELLING Yukari Sugiyama , Mikio Nakamura , Suguru Senda, Michiko Masuda pdf Abstract View : 42 STUDY ON STRENGTH ESTIMATION OF SOIL CEMENT U EMBEDDED PILE METHOD BY ELECTRICAL RESISTIVITY MEASUREMENT Yasuhide Mochida, Masato Matsuura	BITAT OF ENTIFIED B 68-73 pdf downloads: 19 SED IN THE B 74-81
ENVIRONMENTAL PARAMETERS CONTROLLING THE HA THE BRACKISH WATER CLAM CORBICULA JAPONICA ID BY PREDICTIVE MODELLING Yukari Sugiyama , Mikio Nakamura , Suguru Senda, Michiko Masuda Yukari Sugiyama , Mikio Nakamura , Suguru Senda, Michiko Masuda	BITAT OF ENTIFIED © 68-73 pdf downloads: 19 SED IN THE © 74-81 pdf downloads: 19
ENVIRONMENTAL PARAMETERS CONTROLLING THE HA THE BRACKISH WATER CLAM CORBICULA JAPONICA ID BY PREDICTIVE MODELLING Yukari Sugiyama , Mikio Nakamura , Suguru Senda, Michiko Masuda pdf Abstract View : 42 STUDY ON STRENGTH ESTIMATION OF SOIL CEMENT U EMBEDDED PILE METHOD BY ELECTRICAL RESISTIVITY MEASUREMENT Yasuhide Mochida, Masato Matsuura pdf Abstract View : 19 EFFECTS OF ALKALI-ACTIVATED WASTE BINDER IN SOI STABILIZATION	BITAT OF ENTIFIED © 68-73 pdf downloads: 19 SED IN THE © 74-81 pdf downloads: 19

Abstract View : 89

pdf downloads: 68

EVALUATION OF DRAINAGE PROCESS IN POROUS MEDIA BY INVADED PERCOLATION PROBABILITY

Junichiro Takeuchi, Masayuki Fujihara	≧ 90-97
Pdf	
Abstract View : 23	pdf downloads: 24

DAMAGE DETECTION AND LOCALIZATION IN MASONRY STRUCTURE USING FASTER REGION CONVOLUTIONAL NETWORKS

Krisada Chaiyasarn, LuqmanAli, Wasif Khan	₿ 98-105
D pdf	
Abstract View : 98	pdf downloads: 94

STRUCTURAL EVALUATION OF NURUL HAQ SHELTER BUILDING CONSTRUCTED ON LIQUEFACTION PRONE AREA IN PADANG CITY - INDONESIA

Fauzan, Rina Yuliet, Abdul Hakam, Helza Riani	₿ 106-114
Pdf	
Abstract View : 79	pdf downloads: 45

TESTING OF FOAM CONCRETE FOR DEFINITION OF LAYER INTERACTING WITH SUBSOIL IN GEOTECHNICAL APPLICATIONS

Marian Drusa, Jozef Vlcek, Walter Scherfel, Bronislav Sedlar	🖹 115-120
Pdf	
Abstract View : 41	pdf downloads: 28

DEVELOPMENT OF GREEN INFRASTRUCTURE IN URBAN CATCHMENT AREA (CASE STUDY: TANJUNG BARAT SUB-DISTRICT, SOUTH JAKARTA)

Dimas Ario Nugroho, Jachrizal Soemabrata, Hendricus Andy Simarmata, 📄 121-126 Dwinanti Rika Marthanty

🔁 pdf	
Abstract View : 81	pdF downloads: 134

CONSTRUCTION OF EARTH FILL STRUCTURE FOR SMALL FARM

POND BY USING BHUTANESE TRADITIONAL WALL MA METHOD	KING
UENO Kazuhiro , NATSUKA Isamu , SATO Shushi , ONJO Norio , Karma Tshethar , Kelzang Tenzin	₽ 127-132
De pdf	
Abstract View : 26	pdf downloads: 9
RESISTIVITY AND CHARGEABILITY SIGNATURES OF TS	UNAMI
DEPOSITS AT ACEH BESAR AND BANDA ACEH COASTA INDONESIA	AL AREA,
Rosli Saad , Muhammad Syukri , Sabrian Tri Anda, Zul Fadhli	₿ 133-143
pdf	
Abstract View : 49	pdf downloads: 35
SEA-LEVEL RELATED ENGINEERING GEOLOGY AND IN COMPRESSION BEHAVIOUR OF BANGKOK CLAYS	TRINSIC
Krit Saowiang, Pham Huy Giao	₿ 144-153
pdf	
Abstract View : 50	pdf downloads: 30
ADDI ICATION OF DIGITAL ELEVATION METHOD / DEM	
FLOOD ESTIMATION ON UPSTREAM CILIWUNG RIVER, INDONESIA	WEST JAVA,
Sri Legowo, Iwan. K. Hadihardaja, Tunggul Sutan Haji, Enung	₿ 154-165
pdf	
Abstract View : 50	pdf downloads: 47
INFLUENCE OF CLAY CONTENTS ON DRAINED SHEAR PARAMETERS OF RESIDUAL SOIL FOR SLOPE STABILITY	STRENGTH TY
EVALUATION	
Asmaa Gheyath Salih, Arez Mohammed Ismael	₿ 166-172
pdf	
Abstract View : 44	pdf downloads: 33

Jonathan R. Dungca, Juanito Enrico B. Edrada, Vincer	nt A. Eugenio, Roy Adrian 🖹 173-180
凸 pdf	
Abstract View : 86	pdf downloads: 54
VALIDATING THE CURVE OF DISPLACEM	IENT FACTOR DUE TO FULL
SCALE OF ONE PILE ROW NAILED-SLAB	PAVEMENT SYSTEM
Anas Puri, Hary Christady Hardiyatmo, Bambang Suh	nendro, Ahmad Rifa'i 🛛 🗎 181-188
🔁 pdf	
Abstract View : 56	pdf downloads: 19
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon	ITIALLY ZONES IN
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon Pdf Abstract View : 105	ITIALLY ZONES IN
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon pdf Abstract View : 105	ITIALLY ZONES IN
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon pdf Abstract View : 105 REVIEW COLLAPSE MECHANISMS CAUSI	INT OF THE COASTAL ITIALLY ZONES IN Image 189-196 pdf downloads: 87 Image DAMAGE FROM
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon pdf Abstract View : 105 REVIEW COLLAPSE MECHANISMS CAUSI CONTROLLED AND UNCONTROLLED DE Graeme McKenzie, Bijan Samali, Chunwei Zhang	INT OF THE COASTAL ITIALLY ZONES IN Image 189-196 pdf downloads: 87 Ing DAMAGE FROM MOLITIONS Image 197-203
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon pdf Abstract View : 105 REVIEW COLLAPSE MECHANISMS CAUSI CONTROLLED AND UNCONTROLLED DE Graeme McKenzie, Bijan Samali, Chunwei Zhang pdf	INT OF THE COASTAL ITIALLY ZONES IN Image 189-196 pdf downloads: 87 Ing DAMAGE FROM MOLITIONS
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon pdf Abstract View : 105 REVIEW COLLAPSE MECHANISMS CAUSI CONTROLLED AND UNCONTROLLED DE Graeme McKenzie, Bijan Samali, Chunwei Zhang pdf Abstract View : 110	INT OF THE COASTAL ITIALLY ZONES IN IMG DAMAGE FROM MOLITIONS pdf downloads: 65
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon pdf Abstract View : 105 REVIEW COLLAPSE MECHANISMS CAUSI CONTROLLED AND UNCONTROLLED DE Graeme McKenzie, Bijan Samali, Chunwei Zhang pdf Abstract View : 110 DELINEATION OF SUBSURFACE STRUCT	INT OF THE COASTAL ITIALLY ZONES IN I 189-196 pdf downloads: 82 ING DAMAGE FROM MOLITIONS I 197-203 pdf downloads: 62 URES OF SEMANGGOL
EVALUATION OF PHYSICAL DEVELOPME TOURISM REGIONS ON TSUNAMI POTEN PARIAMAN CITY- INDONESIA Dedi Hermon Pdf Abstract View : 105 REVIEW COLLAPSE MECHANISMS CAUSI CONTROLLED AND UNCONTROLLED DE Graeme McKenzie, Bijan Samali, Chunwei Zhang Pdf Abstract View : 110 DELINEATION OF SUBSURFACE STRUCT FORMATION, NORTH PERAK USING MAG	INT OF THE COASTAL ITIALLY ZONES IN Def downloads: 87 ING DAMAGE FROM MOLITIONS Def downloads: 68 URES OF SEMANGGOL SNETIC DATA

ß	pdf	

Abstract View : 45

pdf downloads: 43

THE FLUCTUATION OF DOMESTIC WASTEWATER DISCHARGED

FROM OFFICE BUILDING	
Vandith Va, Ahmad Soleh Setiyawan, Prayatni Soewondo	≌ 210-215
D pdf	
Abstract View : 97	pdF downloads: 37
THE DEVELOPMENT OF JOB COMPETENCY FOR SK	ILLED
TECHNICAL WORKER TOWARDS GREEN TECHNOLO	GY
Affero Ismail, Zeti Kasman, Sri Sumarwati, Faizal Amin Nur Yunus, Noorazman Abd Samad	≌ 216-221
D pdf	
Abstract View : 84	pdf downloads: 85
RUNOFF ON SURFACE OF COMPLEX TOPOGRAPHY DIFFERENT RAINFALL SCENARIO Nguyen Thi Ngoc Anh, Cao Xuan Canh, Agus Yodi Gunawan, Priana	UNDER Sudojo 🖹 222-229
Abstract View : 22	pdf downloads: 12
2D FLOOD INUNDATION SIMULATION BASED ON A PHYSICAL MODEL USING COURSE NUMERICAL GRI Ismail Abustan, Muhammad Azraie Abdul Kadir, Mohd Firdaus Abdu	LARGE SCALE D METHOD Il Razak 🗎 230-236
Abstract View : 50	pdf downloads: 47

Address:

Prof. Dr. Zakaria Hossain Mie University, Japan

Contact Info:

editor@geomatejournal.com

Information :

1.00



University Foundation, Philippines	International Islamic University, Malaysia	Chowdhury , Roosevelt University, USA
Prof. Dr. Isabel Pinto , University of Coimbra, Portugal	Prof. Dr. Mark Jaksa , University of Adelaide, Australia	Prof. Dr. Kaneco Satoshi , Mie University, Japan
Prof. Dr. Junichiro Takeuchi, Kyoto University, Japan	Prof. Dr. Ranjith Pathegama Gamage, Monash University, Australia	Prof. Dr. Kingshuk Roy , Nihon University, Japan
Prof. Dr. Md. Shahin Hossain , Islamic University of Technology, Bangladesh	Prof. Dr. Pedro Arrua , Universidad Tecnológica Nacional, Argentina	Prof. Dr. Miguel A. Pando , Drexel University, Philadelphia, USA
Prof. Dr. Suksun Horpibulsuk, Suranaree University of Technology, Thailand	Prof. Dr. Musharraf Zaman , University of Oklahama, USA	Prof. Dr. Rafiqul Tarefder, University of New Mexico, USA
Dr. Stefano Stacul, University of Pisa Italy	Prof. Dr. Basir Mir, National Institute of ^{I,} Technology Srinagar, India	Prof. Dr. Lily Surayya Eka, State Islamic University Syarif Hidayatullah Jakarta, Indonesia

Address:

Prof. Dr. Zakaria Hossain Mie University, Japan

Contact Info:

editor@geomatejournal.com

Information :

<u>Authors</u> <u>Terms of Use</u> <u>Privacy Policy</u>

© 2011-2022 International Journal of GEOMATE, All rights reserved.

VALIDATING THE CURVE OF DISPLACEMENT FACTOR DUE TO FULL SCALE OF ONE PILE ROW NAILED-SLAB PAVEMENT SYSTEM

*Anas Puri¹, Hary Christady Hardiyatmo², Bambang Suhendro², Ahmad Rifa'i²

¹Faculty of Engineering, Universitas Islam Riau, Indonesia ²Faculty of Engineering, Universitas Gadjah Mada, Indonesia

*Corresponding Author, Received: 10 Oct. 2018, Revised: 07 Jan. 2019, Accepted: 27 Jan. 2019

ABSTRACT: A proposed alternative solution for rigid pavement problem on soft soil is the pavement of Nailed-slab System. It is a kind of developing the rigid pavement. Equivalent modulus of subgrade reaction (k') can be used to analyze Nailed-slab System. This modulus consists of the modulus of subgrade reaction from plate load test (k) and additional modulus of subgrade reaction due to pile installing (Δk) . The Δk can also be determined by using the curve of the displacement factor. This research is aimed to validate the theory of additional modulus of subgrade reaction by using the curve of displacement factor due to the results of a prototype test of Nailed-slab with 1 pile row. The prototypes were constructed on soft clay and the connection between pile and slab was perfect monolithically. These systems were loaded by monotonic loads. Calculated deflections based on the method of the additional modulus of subgrade reaction were compared to the observed deflection and the results from the Finite Element Method. The result shows in good agreement with the observation. The proposed method of analysis was practical in use and timeless consuming. Designing the Nailed-slab by considering a single pile row which used k' will result in design in the safety zone.

Keywords: Nailed-slab system, soft clay, subgrade modulus, deflection, rigid pavement, displacement factor

1. INTRODUCTION

The pavement of Nailed-slab System was developed by changing the shell of the pavement of the chicken foot system (Sistem Cakar Ayam) with short piles in order to gain the efficiency of construction implementation [1]. The Nailed-slab System is not a kind of soil improvement although it is proposed to be applicable for soft soils [2]. This system is a kind of construction to increase the performance of rigid pavement on soft soils. This system consists of a thin pile cap that also serves as a rigid pavement, and short piles attached underneath. The composite system (consists of piles, slab, and soils surrounding the piles) is expected to be formed to bear the loads. The main function of the pile is as a nail to the slab so that the slab remains in contact with the subgrade. The installed piles under the slab also increase the slab stiffness [3]. Then the slab thickness can be decreased. The decreasing of slab thickness can reduce the weight of the structure and will be beneficial for soft soils [4]. Hence, a more durable pavement can be acquired with the result that the pumping could not take place and differential settlement could be reduced. Yet the consolidation problem of soft soils under the construction is not covered by the nailed-slab. This system recommended using thin pile cap (thickness about

12 cm to 25 cm) and short micro piles installed under the pavement slab. Micro piles have 12 cm - 20 cm in diameter, 1 m - 2 m length, and 1 m - 1.5 m pile spacing.

Hardiyatmo [1] conducted several studies on a nailed slab under dynamic loads, and studies on vertical loadings for soft clay were done by Hardiyatmo ([5], [6]), and Puri et al. ([3], [7], [8], [9], [10], [11], [12]), and for stiff lay by Nasibu [13], and Dewi [14]. Nailed-slab System due to tension loading was studied by Puri, et.al. [15] and Puri [16].

Design method by using an equivalent modulus of subgrade reaction (k') in Nailed-slab System analysis was proposed by Hardiyatmo [5]. This modulus consists of the modulus of subgrade reaction from plate load test (k) and additional modulus of subgrade reaction due to pile installing (Δk) . Analysis method in determining the additional modulus of subgrade reaction was also proposed by Hardiyatmo [6]. And it was modified by Puri, et.al. [8] by considering the tolerable deflection or allowable deflection of pavement slab as an approach of safety construction and has good validation due to full-scale test [12].

Additional modulus of subgrade reaction considered displacement factor [6]. This factor is the ratio of the relative displacement between piles and soils (δ_0) and the pile head settlement (δ). The

inverse of the displacement factor is the ratio of δ/δ_0 . The curve of δ/δ_0 ratios was developed by Hardiyatmo [17] based on a full-scale test of single pile Nailed-slab in stiff clay. The pile and slab were connected by bolts. Puri [18] developed a curve of displacement factor ($\alpha = \delta_s/\delta_0$) based on a full-scale test on single pile Nailed-slab in soft clay. Pile and slab were connected perfectly monolithically. It was good validated to full scale of single pile Nailed-slab. The application of this curve on the full-scale Nailed-slab with 1 row of piles will be discussed in this paper.

2. THEORETICAL BACKGROUND

2.1 Equivalent Modulus of Sub Grade Reaction

The analytical approach in determining the equivalent modulus of subgrade reaction (k') is given as follows ([6], [14], [8]):

$$k = k + \Delta k \tag{1}$$

Where k: modulus of subgrade reaction from plate load test (kN/m³), Δk : additional modulus of subgrade reaction due to pile installing under the slab (kN/m³).

Considering the soil bearing pressure under an individual nailed-slab system, Hardiyatmo [6] proposed Eq. (2) in determining the additional modulus of subgrade reaction (Δk). The relative displacement between pile and soil is considered.

$$\Delta k = \frac{\delta_0 A_s}{\delta^2 s^2} \left(a_d c_u + p_0' K_d \tan \varphi_d \right)$$
(2)

Where δ_0 : relative displacement between pile and soil (m), δ : deflection of surface of plate (m), A_s : surface area of pile shaft (m²), s: width area of slab (m), a_d : adhesion factor (non-dimensional), c_u : undrained cohesion (kN/m²), p_o ': average effective overburden pressure along of pile (kN/m²), K_d : coefficient of lateral earth pressure in pile surroundings (non-dimensional), ϕ_d : soil internal friction angle (degree).

The relation between δ_0/δ and slab deflection from pile model with a 4 cm diameter is also given by Hardiyatmo [6]. Hardiyatmo [17] re-published the relation between δ_0/δ and slab deflection for the full-scale model while the pile and slab were connected by a bolt system. The pile diameter was 20 cm dan the length of the pile was varied between 1.0 m to 2.0 m. Puri [18] used the inverse of the ratio of δ_s/δ_0 that is called displacement factor and presented in Figure1. Then, Eq.(2) can be re-written as follows

$$\Delta k = \frac{\alpha f_s A_s}{\delta_a A_{ps}} \tag{3}$$

Where δ_a : tolerable deflection of rigid pavement slab (m). The curve of the displacement factor is

presented in Figure 1. Puri [19] also developed the curve of displacement factor for stiff clay based on Hardiyatmo [6].



Fig.1 Correlation of displacement factor ($\alpha = \delta_0/\delta_s$) and the ratio of δ_s/D for soft clay [18]

For designing purposes, the relative displacement between pile and soil is difficult to define. Puri, et.al. [8] obtained Eq. (4) to define the additional modulus of subgrade reaction which considered the tolerable deflection of rigid pavement slab (δ_a). This approach is called Modified Hardiyatmo method.

$$\Delta k = \frac{0.4 f_s A_s}{\delta_a A_{ps}} \tag{4}$$

Where δ_a : tolerable deflection of rigid pavement slab (m), f_s : ultimate unit friction resistance of pile shaft (kN/m²), A_s the surface area of pile shaft (m²), A_{ps} : area of plate zone which supported by single pile (m²).

Additional modulus of subgrade reaction for Nailed-slab in soft clay is expressed by

$$\Delta k = \frac{0.4a_d c_u A_s}{\delta_a A_{ps}} \tag{5}$$

Where a_d : adhesion factor (non-dimensional), c_u : undrained cohesion (kN/m²).

The modulus of subgrade reaction from the plate load test (k) is usually taken by using a circular plate, and it should be corrected to slab shape of the nailed-slab.

2.2 Analysis of Deflection

Analysis of deflection of a nailed-slab by using equivalent modulus of subgrade reaction has been done by Hardiyatmo ([5], [6]), Puri, et.al. ([7], [8], [9], [10], [11]) and Puri ([2], [23]). This modular was also implemented in Cakar Ayam analysis ([20], [21], [22]). In this paper, the deflection will be analyzed by using Beam on Elastic Foundation (BoEF) and finite element method (FEM). The theory of BoEF can be used to calculate the deflections due to the load acting on platesupported piles ([5], [6], [15], [7], [8], [10], [15]). They used the Hetenyi's formulas. In this paper, the Roark's formulas will be used. The deflection of the finite length of the beam resting on an elastic foundation due to a single concentrated load at any point is explained by using Roark's formulas [23].

Figure 2 shows the approach model of Nailedslab System for BoEF analysis. Figure 2a represents the real construction and Figure 2b represents the approach model. Vertical wall barriers on both ends of the slab are neglected since BoEF cannot accommodate them. Piles are modeled by k' springs. In the BoEF analysis, the k_0 value is changed by k' value which calculated by Eq.(1). Total deflection on the observed point is defined by the superposition method of deflection caused by concentrated load and moment.





b. Approach model

Fig. 2 Approach model of Nailed-slab analysis in BoEF (vertical wall barriers are neglected) [2]

FEM analysis will use the commercial 2D Plaxis software. Nailed-slab will be analyzed by plain strain analysis. The pile will be transformed to continuous wall element by an equivalent thickness on plain strain geometry. Wall thickness will be calculated according to the ratio of pile section area to the soil area which kept constant.

3. TESTING INVESTIGATION

This testing investigation was explained by Puri, et.al ([11], [24]) except for 1-pile row Nailed-slab and here is re-explained.

3.1 Soil Pond and Materials

Nailed-slab will be conducted on soft clay. A 6 m x 3.7 m soil pond was conducted by digging the existing soil until the depth of 2.5 m. On the 2

longer sides was retained by masonry walls and supported by some temporary girder. The anchorage system was built near the pond. Separator sheets were set on the pond walls and base to avoid the effects of surrounding existing soils. A 2.15 m of the depth of test box was filled by soft clay which is taken from District Ngawi, East Java. Indonesia. The soft clav properties are presented in [11] and [12]. There was soft clay with plasticity index 59.98% and undrained shear strength 20.14 kN/m². The slab and piles were reinforced concrete. The concrete strength characteristic of slab and piles were 29.2 MPa and 17.4 MPa respectively. The flexural strength of the slab was 4,397.6 kPa. The coefficient of subgrade reaction based on standard plate load test was 15,000 kPa/m. This coefficient became 2,750 kPa/m after correction due to the dimension and shape of nailed-slab (according to [25]).

3.2 Dimension of Nailed-slab

Test on 1 pile row Nailed-slab consisted of the slab with 600 cm \times 120 cm \times 15 cm in dimension. Pile length was 150 cm and the pile spacing was 120 cm. This model was obtained by cutting the 600 $cm \times 354 cm \times 15 cm$ Nailed-slab became 3 parts where each part consisted of one pile row. The tested 1 pile row Nailed-slab was the middle one with slab dimension 600 cm \times 120 cm \times 15 cm as shown in Figure 3. Test on 1 pile row Nailed-slab consisted of the slab with 600 cm \times 120 cm \times 15 cm in dimension. Pile length was 150 cm and the pile spacing was 120 cm. This model was obtained by cutting the 600 cm ×354 cm × 15 cm Nailedslab became 3 parts where each part consisted of one pile row. The tested 1 pile row Nailed-slab was the middle one with slab dimension 600 cm \times $120 \text{ cm} \times 15 \text{ cm}$ as shown in Figure 3.

3.3 Testing Procedures

The steps in the construction of Nailed-slab can be briefly described as follows: the pond was filled by soft clay until the soil thickness reach 2.15 m. Soft clay was spread about 15 cm in thickness per layer with controlled water content, and then it was compacted by 3 passing of manual compaction. Each soil layer thickness was decreased to about 10 cm per layer. Soft clay was cured by covering its surface with plastic sheet and wet carpet. Some soil investigations were conducted, i.e. soil boring, vane shear test, CBR test, and plate load test. After that, a pile was driven by the pre-drilled method and then continued by hydraulic jacking until the pile top reaches the design level.

The pile was tested for compression bearing

capacity and tension capacity. The soil was excavated for thickening slab. The 5 cm lean concrete then poured on the soil surface and continued by conducting the CBR test and plate load test after 3 days. The slab and vertical wall barrier reinforcement rebar were assembled. And then concrete was poured for the slab. The slab was cured by wet carpet and after 28 days of concrete age, the loading set up was assembled. Loading test was conducted on the slab for different load positions (Point A and C in Figure 3a). Loads were transferred to the slab surface by using a circular plate with 30 cm in diameter (the plate represents the single wheel load contact area). Then the instrumentations were recorded. Some photographs in construction and testing were presented in Figure 4.



Fig.3 Schematic diagram of full-scale Nailed-slab with 1 pile row [2]

3.4 Analysis Method

The numerical analysis will be conducted by using BoEF Analysis version 1.4 and 2D Plaxis v. 8.6. Piles and soils were approached by vertical spring k' in BoEF analysis. In 2D Plaxis FEM (plain strain analysis), the soft clay was modeled by Mohr-Coulomb in un-drained condition. All structural elements were modeled by plate element in linear-elastic behavior. Lean concrete was modeled by soil with the linear-elastic non-porous material. All structural elements were modeled by linear-elastic behavior. This 2D FEM used plain strain analysis type. Soil parameters and idealization of structural elements are presented in Table 1 and 2 respectively. The thickening slab was ignored since it could not be modeled by Plaxis 2D.



Fig.4 Photographs of loading tests on full-scale Nailed-slab with 1 pile row (point C)

4. RESULTS AND DISCUSSIONS

4.1 The 2D Numerical Analysis of 1 Pile-row Nailed-slab

The result shows that the vertical wall barrier was not significant effect (Figure 5a). The deformed mesh is shown in Figure 6 which the end of the slab was uplift. It is quite different with the result in a full-scale test. It is concluded that the Plaxis 2D could not model the vertical wall barrier which lower position than slab level, as well as could not model the thickening slab. The distribution of deflection along the slab will be discussed in section 4.2.

Lean concrete can reduce deflection and it significant under centric load (Figure 5b). Reduced deflection tends to be higher by increasing the thickness of lean concrete.

4.2 Validation of the Method of Preliminary Design Based on *k*'

The structure of pavement of full-scale Nailed-slab System was calculated to find deflections and internal forces by using an equivalent modulus of subgrade reaction (k^2) . The soil modulus of subgrade reaction for 1.20 m slab width was 3,300 kPa/m. Calculations were run by BoEF software. Design load was 40 kN single wheel load. Table 3 gives calculating results of k^2 where calculated by using Eq.(5) and Figure 1.

Parameters	Name/ Notation	Soft clay	Sand	Unit
Material model	Model	Mohr-Coulomb	Mohr-Coulomb	-
Material behavior	Туре	Undrained	Drained	-
Saturated density	∕∕sat	16.30	18.00	kN/m ³
Dry density	γa	10.90	20.00	kN/m ³
Young's Modulus	E	1,790.00	42,750.00	kPa
Poisson's ratio	V	0.45	0.35	-
Undrained cohesion	Cu	20.00	1.00	kPa
Internal friction angle	ϕ	1.00	47.80	0
Dilatancy angle	Ψ	0.00	2.00	0
Initial void ratio	e 0	1.19	0.50	-
Interface strength ratio	R	0.80	0.70	

Table 1 Model and parameters of soil

Table 2 Model and parameters of structural elements in FEM 2D plain strain

Parameters	Name/	Lean	Lean Structural elements		ts	Unit
	Notation	concrete (LC)	Slab	Vertical wall barrier	Pile	
Material model	Model	Volume element	Plate	Plate	Plate	-
Material behavior	Туре	Elastic	Elastic	Elastic	Elastic	-
Normal stiffness	EA	-	4,554,000	3,795,000	616,696	kN/m
Flexural rigidity	EI	-	8,539	4.941	75,655	kNm²/m
Equivalent thickness	d	-	0.15	0.125	0,027	m
Weight	W	-	3.60	3.00	29.12	kNm/m
Poisson's ratio	v	0.2	0.15	0.15	0.20	-
Unit weight	γ	22	24	24	24	kN/m ³
Young's Modulus	Ε	17,900	25,300	25,300	19,600	MN/m ²
Interface strength ratio	R	0.80	0.80	0.80	0.80	-

Table 3 Equivalent	modulus of	f subgrade	reaction for1	pile row number
		/		

Load position	Eq. (5)			Formula Hardiyatmo and Figure 1		
	k (kN/m ³)	$\Delta k (\mathrm{kN/m^3})$	k' (kN/m ³)	k (kN/m ³)	$\Delta k (\mathrm{kN/m^3})$	k' (kN/m ³)
Centric	3,300	1,175	4,755	3,300	380	3,680
Edge	3,300	1,175	6,710*	3,300	380	5,520*

Calculated results based on Eq.(5) and Figure1 were good agreement with observation (Figure7). Calculated results based on Figure1 were higher than results based on Eq.(5) on the average 13.13%. It is caused by the equivalent modulus of subgrade reaction based on Figure1 higher than based on Eq.(5). Calculated deflections based on Eq.(5) and Figure1 were higher than an observation on the average 51.37% and 66.20% respectively. These over-estimated results were caused of neglected to vertical wall barrier and thickening slab. BoEF distributes a concentrated load P over slab width, so the working load does not concentrate load in analyzing. It also occurs to edge loads. The

calculated deflections are linear-elastic and agreed with the assumption of both methods. Results from 2D FEM were very close to observations (Figure 7). However, the distributions of deflections along the slab show that there are uplifts on the ends of the slab (Figure 7b and 7d), but the soil was kept in contact with the slab (Figure 6a and 6b). It is supposed that the software could not model the vertical wall barrier.

Nailed-slab System under a centric load of single wheel load (40 kN), the maximum calculated deflection was 2.60 mm and it did not exceed the tolerable deflection (δ_a) = 5 mm.



Fig.5 *P*- δ relationships from FEM 2D, a) Effect of vertical wall barrier for edge load on C, b) Effect of lean concrete for the concentric load on A



Fig.6 Deformed mesh of 1-pile row Nailed-slab, a) for concentric load on A, b) for edge load on C



Fig.7 Calculated deflections for full scale Nailed-slab with 1 pile row; a) P- δ concentric load, b) Deflection along slab- P_{max} concentric, c) P- δ edge load, d) Deflection along slab- P_{max} edge

Maximum calculated deflection due to edge load was 7.10 mm > δ_a , but then the observed deflection for centric and edge load was only 1.21 mm and 2.04 mm respectively. Building on these

facts, the design of Nailed-slab System is sufficiency. And by considering that in the field the Nailed-slab will be built in great quantities of piles, then the designing based on single pile row will result in a design in a safety zone. Therefore, the proposed formula and designing by considering single pile row were very sufficiency and will result in a design in a safety zone. And so do, it is easier in conducting the analysis.

5. CONCLUSIONS

According to loading test results on full-scale Pavement of Nailed-slab with 1 pile row, analysis results, and discussion, several important conclusions can be concluded as follows

- 1. The tested model and full-scale Nailed-slab system on soft clay showed the smooth deflected bowl. It indicates that all piles abled to give similar responses. Compression and pull out the capacity of piles were mobilized that made the slab keep contact with soil.
- 2. Based on observation, the system has a higher stiffness to bear the loads. It was evidenced by linear elastic-response until load 80 kN. The higher stiffness of the system was experienced by small deflection about 2 mm due to centric load (P = 80 kN \approx 2xsingle wheel load).
- 3. Installed piles under the slab which embedded into the soils increased slab stiffness. It could be expressed by Δk . Such was the case that increasing in pile row number could increase the stiffness of the system which represented by k'.
- 4. Formula and curve of displacement factor for determining the additional modulus of subgrade reaction could be used for analyzing the Nailed-slab System. Both were validated by observation, BoEF analysis, and 2D FEM. Analysis results were good agreement with observation, although tends less satisfy for edge loads. Employing k' in BoEF analysis was sufficiency enough. Into the bargain, the proposed method of analysis was practical in use and timeless consuming. Designing the Nailed-slab by considering a single pile row which used k' will result in safety design.

Further research and developing the equivalent modulus of subgrade reaction for edge loads is necessary.

6. ACKNOWLEDGMENTS

The authors acknowledge the financial support from the Directorate General of Research and Technology and the Higher Education Republic of Indonesia number SP DIPA-023.04.1.673453/2015.

7. REFERENCES

 Hardiyatmo, H.C. Nailed-slab System for Reinforced Concrete Slab on Rigid Pavement. Proc. of National Seminar on Appropriate Technology for Handling Infrastructures, MPSP JTSL FT UGM., Yogyakarta, 2008, Indonesia, pp. M-1—M-7.

- [2] Puri, A. Behavior of Pavement of Nailed-slab System on Soft Clay, Dissertation, Doctoral Program of Civil Engineering, Universitas Gadjah Mada, Yogyakarta, 2015.
- [3] Puri, A., Hardiyatmo, C. H., Suhendro, B., Rifa'i, A. Experimental Study on Deflection of Slab which Reinforced by Short Friction Piles in Soft Clay, Proc. of 14th Annual Scientific Meeting, HATTI, Yogyakarta, 10-11 February 2011, pp. 317-321.
- [4] Hardiyatmo, H.C., and Suhendro, B. Pile Foundation with Thin Pile Cap as an Alternative to Solve Problems of Building on Soft Soils, Report of Competitive Grant Research of Higher Education, Institute for Research and Community Service, Universitas Gadjah Mada, Yogyakarta, 2003.
- [5] Hardiyatmo, H.C. Method to Analyze the Slab Deflection by Using Equivalent Modulus of Subgrade Reaction for Flexible Slab Structure, Dinamika Teknik Sipil, 2009, Vol.9 No.2, pp. 149-154.
- [6] Hardiyatmo, H.C. Method to Analyze the Deflection of the Nailed Slab System, IJCEE-IJENS, 2011, Vol 11. No. 4, pp. 22-28. <u>http://ijens.org/IJCEE%20Vol%2011%20Issu</u> <u>e%2004.html</u>.
- [7] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A. Contribution of Wall Barrier to Reduce the Deflection of Nailed-Slab System in Soft Clay (Indonesian language), Proc. of 9th Indonesian Geotech. Conf. and 15th Annual Scientific Meeting, HATTI, Jakarta, 7-8 December 2011, pp. 299-306.
- [8] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A. Determining Additional Modulus of Subgrade Reaction Based on Tolerable Settlement for the Nailed-slab System Resting on Soft Clay, IJCEE-IJENS, 2012, Vol. 12 No. 3, pp. 32-40. <u>http://ijens.org/ IJCEE%20Vol%2012%20Issue%2003.html</u>.
- [9] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A. Application of The Additional Modulus of Subgrade Reaction to Predict The Deflection of Nailed-slab System Resting on Soft Clay Due to Repetitive Loadings, Pros. Pertemuan Ilmiah Tahunan ke-16 HATTI, Jakarta, 4 December 2012, pp. 217-222.
- [10] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A. Pile Spacing and Length Effects Due To the Additional Modulus of Subgrade Reaction of the Nailed-Slab System on the Soft Clay, Proc. of 13thInternational Symposium on Quality in Research (QiR), Yogyakarta, 25-28 June 2013, pp. 1032-1310.

http://qir.eng.ui.ac.id/wpcontent/unloads/2017/03/OiR.

content/uploads/2017/03/QiR-2013.pdf.

- [11] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A. Application of Method of Nailedslab Deflection Analysis on Full Scale Model and Comparison to Loading Test, Proc. the 7th National Conference of Civil Engineering (KoNTekS7), Universitas Negeri Sebelas Maret, Surakarta, 24-26 October 2013, pp. G201-G211.
- [12] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A.Behavior of Full Scale Nailed-slab System with Variation on Load Positions, Proc. 1st International Conference on Infrastructures Development, Universitas Muhammadiyah Surakarta, Solo, 1-3 November 2013, pp. 26-36.
- [13] Nasibu, R. Study on Modulus of Subgrade Reaction Due to Effect of Pile Attached Under Plate (Loading Test on Fullscale). Master Theses. Postgraduate Program of Engineering, Universitas Gadjah Mada, Yogyakarta, 2009.
- [14] Dewi, D.A. Study on Effect of Single Pile Due to the Value of Equivalent Modulus of Subgrade Reaction from Full-scale Loading Tests. Master Thesis, Postgraduate Program Universitas Gadjah Mada, Yogyakarta, 2009.
- [15] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A.Pull out Test of Single Pile Row Nailed-slab System on Soft Clay, Proc. The 14th International Conference on Quality in Research (QiR), Universitas Indonesia, Lombok, 10-13 August 2015, pp. 63-68
- [16] Puri, A. Behavior of Uplift Resistance of Single Pile Row Nailed-slab Pavement System on Soft Clay Sub Grade, Proc. The 3rd Asia Future Conference, Kitakyushu, 29 September – 3 October 2016, pp. 1226-1230.
- [17] Hardiyatmo, C.H. Designing of Pavement Roads and Soil Investigation: flexible pavement, rigid pavement, modified chicken foot foundations, the nailed-slab system (Indonesian language), Gadjah Mada University Press, Yogyakarta, 2011.
- [18] Puri, A. Developing The Curve of Displacement Factor for DeterminationThe Additional Modulus of Subgrade Reaction on Nailed-Slab Pavement System, International Journal of Technology (IJTech), 2017, Vol. 1,

pp. 122-131. ISSN 2086-9614. http://ijtech.eng.ui.ac.id/article/view/232.

- [19] Puri, A. Differentiation of Displacement Factor for Stiff and Soft Clay in Additional Modulus of Subgrade Reaction of Nailed-slab Pavement System, Proc. of the Second International Conference on the Future of ASEAN (ICoFA) 2017 – Volume 2, Universiti Teknologi MARA, Perlis, 15-16 August 2017. Springer.
- [20] Puri, A., Ardiansyah, R. Calculation The Edge of Slab Deflection of Modified Cakar Ayam System By Applying The Displacement Factor from Puri's Graph. Proc.the 15th International Symposium in QiR (Quality in Research), Nusa Dua, Bali, 24-27 July 2017, Indonesia. doi. https://doi.org/10.14716/ijtech.v8i1.1688
- [21] Afriliyani, N., Puri, A., Ardiansyah, R. Penerapan Modulus Reaksi Subgrade Ekivalen Metode Puri, dkk (2012) dalam Perhitungan Lendutan Pelat pada Perkerasan Sistem Cakar Ayam Modifikasi. Prosiding Konferensi Nasional Teknik Sipil dan Perencanaan, Universitas Islam Riau, Pekanbaru, 9 Februari 2017, pp. 29-35.
- [22] Agustin, D. R., Puri, A., Ardiansyah, R. Perhitungan Lendutan Perkerasan Jalan Sistem Cakar Ayam Modifikasi dengan Variasi Faktor Aman pada Tambahan Modulus Reaksi Subgrade. J. Saintis, Vol 17 No. 1, 2017, pp. 15-23. <u>http://journal.uir.ac.id/index.php/saintis/article/view/1761</u>.
- [23] Young, W.C., Budynas, R.G. Roark's Formula for Stress and Strain. 7th ed., McGraw-Hill, New York, 2002.
- [24] Puri, A., Hardiyatmo, H.C., Suhendro, B., Rifa'i, A. Behavior of Nailed-slab System on Soft Clay Due to Repetitive Loadings by Conducting Full-Scale Test, IJCEE-IJENS, 2014, Vol. 14 No. 03, pp. 24-30. http://ijens.org/IJCEE%20Vol%2014%20Issu e%2006.html.
- [25] Das, B.M. Principle of Foundation Engineering, 7ed., Cencage Learning, Stamford, 2011.

Copyright © Int. J. of GEOMATE. All rights reserved, including the making of copies unless permission is obtained from the copyright proprietors.

SCIMAGO INSTITUTIONS RANKINGS also developed by scimago: Ш **SJR** Scimago Journal & Country Rank Home Journal Rankings **Country Rankings** Viz Tools Help About Us (i) X From The Industry Leader CrowdStrike Is Independently Tested & Proven to Stop Malware & Breaches. CrowdStrike® Open

International Journal of GEOMATE

COUNTRY	SUBJECT AREA AND CATEGORY	PUBLISHER	H-INDEX
Japan	Agricultural and Biological Sciences Soil Science Earth and Planetary Sciences Geotechnical Engineering and Engineering Geology Engineering Building and Construction Environmental Science Environmental Engineering	GEOMATE International Society	21
PUBLICATION TYPE	ISSN	COVERAGE	INFORMATION
Journals	21862982, 21862990	2011-2021	Homepage How to publish in this journal
			editor@geomatejourn al.com



Open

SCOPE

The journal aims to become an efficient mean of publishing and distributing high quality information from the researchers, scientists and engineers. The main scopes are as follows: Advances in Composite Materials- Computational Mechanics-Foundation and Retaining Walls- Slope Stability- Soil Dynamics- Soil-Structure Interaction- Pavement Technology- Tunnels and Anchors- Site Investigation and Rehabilitation- Ecology and Land Development- Water Resources Planning- Environmental Management - Public Health and Rehabilitation- Earthquake and Tsunami Issues- Safety and Reliability- Geo-Hazard Mitigation-Case History and Practical Experience- Others

ίx

 \bigcirc Join the conversation about this journal



B

0



Cites / Doc. (4 years)
Cites / Doc. (3 years)
Cites / Doc. (2 years)

2019

2021

2017

2011

2013

2015



Metrics based on Scopus® data as of April 2022

D dwikoranto

Thank you, I started joining to get information about journals.

(

Open