





Home
All Journals
Petroleum Science and Technology
Editorial Board

Petroleum Science and Technology

Publish with us Submit an article ~

About this journal ~

Explore Browse all articles & issues

Latest issue

Subscribe Alerts & RSS feed v

+ Purchase a subscription

Ready to submit?

Start a new manuscript submission or continue a submission in progress

Go to submission site 🖸

Submission information

- > Instructions for authors
- > Editorial policies 🗹

Editing services

Editing services site I

About this journal

- > Journal metrics
- > Aims & scope
- > Journal information
- > Editorial board

> News & call for papers

> Advertising information

Editorial board

EDITOR-IN-CHIEF

Dr. Berna Hasçakır Texas A&M University, Texas, United States

EDITOR EMERITUS

Dr. James Speight Dr. Dandina Rao

ADVISORY COUNCIL

Dr. Martin Blunt - *Imperial College London, UK* Dr. Ioannis Economou - *Texas A&M University at Qatar, Qatar* Dr. Anthony R. Kovscek - *Stanford University, USA* Dr. Cem Sarica - *The University of Tulsa, USA* Dr. Catalin Teodoriu - *The University of Oklahoma, USA* Dr. Carlos Torres-Verdin - *The University of Texas at Austin, USA*

ASSOCIATE EDITORS & EDITORIAL BOARD MEMBERS

Dr. Simon Ivar Andersen - Technical University of Denmark, Denmark Dr. Hadi Belhaj - Khalifa University, UAE Dr. Prem K. Bikkina - Oklahoma State University, USA Dr. Lante A. Carbognani - University of Calgary, Canada Dr. Chao Gao - Occidental Petroleum, USA Professor Elcio Cruz de Oliveira - Petrobras Transporte S.A.-Transpetro and Pontifical Catholic University of Rio de Janeiro, Brazil Dr. Carlos Lira Galeana - Instituto Mexicano del Petroleo, Mexico Dr. Nour Sh. El-Gendy - Egyptian Petroleum Research Institute, Egypt Dr. Sanket Joshi - Sultan Qaboos University, Sultanate of Oman Dr. Taniya Kar - Reservoir Engineering Research Institute (RERI), USA Dr. Yousef Kazemzadeh - Tehran University, Iran Dr. Ufuk Kılıçaslan - Turkish Petroleum Corporation (TPAO), Turkey Dr. Mustafa Verşan Kök - Middle East Technical University, Turkey Dr. Gavin Liu - University of North Dakota, Grand Forks, USA Dr. Brij Maini - University of Calgary, Canada Dr. Hamzeh Mehrabi - University of Tehran, Iran Dr. Isabel Merdrignac - IFPEN, France Dr. Rouzbeh G. Moghanloo - University of Oklahoma, USA Dr. Tarek Youssef Morsy - Egyptian Petroleum Research Institute, Egypt Dr. Nam Nguyen-Dang - Institute of Fundamental and Applied Sciences, Duy Tan University, Viet Nam

Dr. Rita Okoroafor - Texas A&M University, USA

Dr. Pramod Patil - Rock-Oil Consulting Group LLC, Sugar Land, USA

Dr. Ray (Zhenhua) Rui - Massachusetts Institute of Technology, USA

Dr. Durlubh K. Sharma - Centre for Energy Studies, India

Dr. Lei Wang - Nazarbayev University, Astana, Kazakhstan

- Dr. Renfeng Yang China National Offshore Oil Corporation Research Institute, China
- Dr. Qingwang (Kevin) Yuan Texas Tech University, USA
- Dr. Gholamreza Zahedi Missouri University of Science & Technology, USA





Information for	Open access
Authors	Overview
R&D professionals	Open journals
Editors	Open Select
Librarians	Dove Medical Press
Societies	F1000Research
Opportunities	Help and information
Reprints and e-prints	Help and contact
Advertising solutions	Newsroom
Accelerated publication	All journals
Corporate access solutions	Books

Keep up to date

Register to receive personalised research and resources by email



Copyright © 2022 Informa UK Limited Privacy policy Cookies Terms &

(CC) Taylor & Portaic Group CHC subarrest cares

conditions Accessibility

Registered in England & Wales No. 3099067 5 Howick Place | London | SW1P 1WG





Home
All Journals
Petroleum Science and Technology
List of Issues
Volume 40, Issue 1

Petroleum Science and Technology

Publish Explore Subscribe with us Browse all + Purchase a Latest Submit an Alerts & About this articles & issues issue subscription RSS feed ∨ article ~ journal ~



Browse this journal

- > Latest articles
- Current issue
- List of issues
- > Special issues
- > Open access articles
- Most read articles
- Most cited articles

Sample our Economics, Finance, Business & Industry Journals >> Sign in here to start your access to the latest two volumes for 14 days

Petroleum Science and Technology, Volume 40, Issue 1 (2022)

See all volumes and issues

<	Volume 40, 2022	Vol 39, 2021	Vol : >
< 5	sue Issue Issue Issu 16 15 14 1	u (> 3	

Geology/Geochemistry

Article Applying artificial intelligent and empirical techniques for prediction of total organic carbon content from wireline data: A case study from Pabdeh Formation in Mansuri oilfield, SW Iran >

Bahram Alizadeh, Seyed Rasoul Seyedali, Iman Zahmatkesh & Hashem Sarafdokht

Pages: 1-17

Published online: 05 Nov 2021



Article

Comprehensive Classification of Low and Ultra-Low Permeability Sandstone Reservoirs in Jidong Oilfield, China >

Lin Shang, Xuejun Chang, Qunhui Wang, Yanchun Sun, Yao Zhao, Jianpeng Xing, Dongliang Jiang & Hao Chen

Pages: 18-40

0

Published online: 04 Oct 2021

111

0

Light oil EOR

Recent advances in ASP flooding and the implementation of nanoparticles to enhance oil recovery: a short review > Agus Arsad, Hasanain A. Al-Jaber, Radzuan Junin, Sulalit Bandyopadhyay, Abdulmunem R. Abdulmunem, Jeffrey Onuoma Oseh, Agi Augustine, Muslim Darbi Abdurrahman, Evizal Abdul Kadir & Sharul Kamal Abdul Rahim Pages: 41-58 Published online: 15 Nov 2021 251 1 Views 1 Altmetric

Oil chemistry/Catalysis



Jianqi Xu, Guolin Jing, Tie Liu, Yang Liu, Liang Yanheng & Yihai Yang

Pages: 59-72

Published online: 25 Nov 2021

29800ViewsCrossRef citationsAltmetric

Factors influencing production of JET fuel by hydrocracking >

Hugo Kittel, Daniel Kadleček & Pavel Šimáček

Pages: 73-91

Published online: 22 Oct 2021

175	0	0
Views	CrossRef citations	Altmetric

Article Compared efficiency of sustainable and conventional treatments of saline oilv wastewater rejected by netroleum industry in Algerian https://www.tandfonline.com/toc/lpet20/40/1 muser muter rejected by performant managery managerian

Sahara >

Sadek Igoud, Djamel Zeriri, Belgassim Boutra, Amel Mameche, Yanal Benzegane, Moufid Belloula, Lamia Benkara, Lamine Aoudjit & Aicha Sebti

Pages: 92-106

Published online: 24 Nov 2021

68	0	0
Views	CrossRef citations	Altmetric

Drilling/Production

Article

Application of particle mutation in drilling accidents diagnosis of Bohai shallow layers >

Xie Tao, Chen Zhuo, Liu Hailong, Lin Hai & Zhang Qilong

Pages: 107-128

Published online: 12 Oct 2021

77	0	0
Views	CrossRef citations	Altmetric

Explore articles



Article | Published online: 12 Nov 2022

Rejuvenate the aged asphalt with functional oil emulsion >

Xiaobing He et al.

Article | Published online: 12 Nov 2022

Predicting the brittleness of sandstones from the Leeb hardness test >

Utku Sakız

Article | Published online: 12 Nov 2022

View all latest articles>

Information for	Open access
Authors	Overview
R&D professionals	Open journals
Editors	Open Select
Librarians	Dove Medical Press
Societies	F1000Research
Opportunities	Help and information
Reprints and e-prints	Help and contact
Advertising solutions	Newsroom
Accelerated publication	All journals
Corporate access solutions	Books

Keep up to date

Register to receive personalised research and resources by email



Copyright © 2022 Informa UK Limited Privacy policy Cookies Terms &

(CC) Taylor & Formate Group C = C summer terms

conditions Accessibility

Registered in England & Wales No. 3099067 5 Howick Place | London | SW1P 1WG





Petroleum Science and Technology

ISSN: (Print) (Online) Journal homepage: https://www.tandfonline.com/loi/lpet20

Recent advances in ASP flooding and the implementation of nanoparticles to enhance oil recovery: a short review

Agus Arsad, Hasanain A. Al-Jaber, Radzuan Junin, Sulalit Bandyopadhyay, Abdulmunem R. Abdulmunem, Jeffrey Onuoma Oseh, Agi Augustine, Muslim Darbi Abdurrahman, Evizal Abdul Kadir & Sharul Kamal Abdul Rahim

To cite this article: Agus Arsad, Hasanain A. Al-Jaber, Radzuan Junin, Sulalit Bandyopadhyay, Abdulmunem R. Abdulmunem, Jeffrey Onuoma Oseh, Agi Augustine, Muslim Darbi Abdurrahman, Evizal Abdul Kadir & Sharul Kamal Abdul Rahim (2022) Recent advances in ASP flooding and the implementation of nanoparticles to enhance oil recovery: a short review, Petroleum Science and Technology, 40:1, 41-58, DOI: <u>10.1080/10916466.2021.1980013</u>

To link to this article: <u>https://doi.org/10.1080/10916466.2021.1980013</u>



Published online: 15 Nov 2021.

-	-
r	
	21
~	

Submit your article to this journal 🕝

Article views: 80

\mathbf{O}

View related articles



View Crossmark data 🗹

REVIEW





Recent advances in ASP flooding and the implementation of nanoparticles to enhance oil recovery: a short review

Agus Arsad^a (**b**), Hasanain A. Al-Jaber^a, Radzuan Junin^b, Sulalit Bandyopadhyay^c, Abdulmunem R. Abdulmunem^d (**b**), Jeffrey Onuoma Oseh^b (**b**), Agi Augustine^b, Muslim Darbi Abdurrahman^e, Evizal Abdul Kadir^e, and Sharul Kamal Abdul Rahim^f

^aUTM-MPRC Institute for Oil and Gas, Faculty of Engineering, Universiti Teknologi Malaysia, UTM Johor Bahru, Johor, Malaysia; ^bSchool of Chemical and Energy Engineering, Faculty of Engineering, Universiti Teknologi Malaysia, UTM Johor Bahru, Johor, Malaysia; ^cDepartment of Chemical Engineering, Norwegian University of Science and Technology, Trondheim, Norway; ^dElectromechanical Engineering Department, University of Technology, Baghdad, Iraq; ^eUniversitas Islam Riau, Pekanbaru, Indonesia; ^fWireless Communication Centre, Faculty of Engineering, Universiti Teknologi Malaysia, UTM Skudai, Johor, Malaysia

ABSTRACT

Although the world is turning to renewables as a clean alternative source of energy, reliance on oil is expected to continue for more decades. Enhanced oil recovery (EOR) is an efficient way to recover oil after implementing initial methods. Alkali-surfactant-polymer flooding (ASP) has acquired much interest together with nano-fluid that involves using nano metallic oxides in EOR. Nanoparticles have proved their effectiveness in reducing interfacial tension at the interface between the oil and water and have been used with water, polymers, surfactants, alkaline, or a mixture of these components. Incremental oil recovery from applying ASP floods has exceeded 20% OOIP, and this is considered promising performance for unlocking oil reserves for many years to come. Despite that, ASP flooding nowadays faces big challenges presented by fluctuating oil prices, scaling and corrosion of the lifting system, and the formation of relatively strong emulsions that need high-cost treatment after oil production. This review emphasizes ASP flooding and the ASP flooding and the implementation of nanoparticles in extracting more oil using different chemical agents and sheds light on improving the recovery ratio. This study also explains the challenges that face each process and the steps that should be taken in order to overcome these challenges.

KEYWORDS

enhanced oil recovery; alkali-surfactant-polymer flooding; nano-fluid injection; optimum flooding; chemical flooding with nanoparticles

1. Introduction

Crude oil has continued to exist as the primary energy source despite other methods of generating energy from other sources. Due to a reduction in oil

CONTACT Agus Arsad agus@utm.my DUTM-MPRC Institute for Oil and Gas, Faculty of Engineering, Universiti Teknologi Malaysia, UTM Johor Bahru, Johor, Malaysia. © 2021 Taylor & Francis Group, LLC

production in some areas, modern technologies are needed to increase production and balance global demand. Some of these techniques involve adding a surfactant or adding it together with a polymer to the reservoir in a process called surfactant–polymer (SP) flooding. Another combination employs the addition of an organic or inorganic base to the water together with a surfactant or with a surfactant–polymer formulation to produce the so-called alkali–surfactant–polymer (ASP) flooding.

In ASP flooding, the alkaline reacts with naphthenic acids available in crude oil to generate in situ surfactant mixed with the original present surfactant (Khan et al. 2009). A surfactant's presence is important to reduce the interfacial tension (ITF) between the oil and the water liquids (Cheng et al. 2014). The presence of polymer in water solution functions as a modifier that increases the viscosity of water and improves the sweep efficiency, consequently increases the flow rate of oil.

Due to the limitation of applying ASP flooding in a large-scale operation, the urgency to find a new alternative has increased. Nanoparticles (NPs) materials, owing to their large surface area to volume ratio, are widely researched for use in EOR processes (Mokhatab et al. 2006; Cheraghian et al. 2014; Nazari Moghaddam et al. 2015; Cheraghian et al. 2017; Khadem Olhosseini et al. 2020). The latest development in nanotechnology includes adding NPs with polymers and surfactants to form a novel combination that can be used as an injectant. For example, Gbadamosi et al. (2019) studied the use of aluminum oxide (Al_2O_3) nanoparticles as a chemical agent with hydrolyzed polyacrylamide (HPAM) solution. The results of their experimental study indicated that Al_2O_3 was a good agent for EOR operations.

An inorganic nano-silica (SiO₂), metal oxide titanium (TiO₂) NPs and Al_2O_3 NPs were used by many researchers. For instance, Esfandyari Bayat et al. (2014) use them in an intermediate-wet limestone at elevated temperatures between 26 and 60 °C. They found that these NPs lowered the IFT between oil and water phases and, at the same time, modified the sandstone core wettability at nearly the entire examined temperatures. Youssif et al. (2018) investigated the effect of nano-silica with concentrations (0.01, 0.05, 0.1, and 0.5 wt.%) in the flooding stream to improve oil recovery. The optimum concentration of silica nano-fluid corresponding to the maximum oil recovery was 0.1 wt.%. Nano-silica helped in reduced the oil–water IFT and surfactant adsorption on the rock surface.

NPs are essential for a broad range of commercial and research applications due to their physical characteristics and properties. Cheraghian et al. (2020) stated that the demand for NPs for use in EOR is very high. Their study focused on a review of the application of NPs in the flooding process and the effect of NPs on wettability and IFT measurements. In the same regard, it also found the potential of adding nano-titanium dioxide as an agent for improving the efficiency of surfactant flooding in a five-spot glass micromodel. The newly developed nano-surfactant solutions with 1600–2000 ppm sodium dodecyl sulfate were tested. Their experiments showed an improvement for heavy oil recovery using TiO_2 NPs at around 51%. Also, Cheraghian and Tardasti (2012) tested two NPs dissolved in water and injected titanium dioxide and fumed silica into a simulated environment. Through their experiments, it was possible to demonstrate that flows with NPs, especially titanium dioxide, had increased oil recovery. It is concluded that using NPs in water and polymer flooding can benefit the recovery process.

Bera et al. (2020) tested the performance of guar gum with and without silica nanoparticles at different temperature ranges $(25-75 \,^{\circ}\text{C})$. Their experiments were conducted using 2000 ppm brine, 4000 ppm guar gum, 0.2 wt.% silica nanoparticles in distilled water as test fluids to recover a waxy crude oil from sandstone cores. Their results showed that guar gum that contains 0.2 wt.% silica nanoparticles was efficient in improving oil recovery by around 44.3% of OOIP. In their efforts to find the benefits of adding nanoparticles and nano-dispersions to enhance oil recovery, Bera and Belhaj (2016) indicated in their article that nanoparticles are effective to recover around 10% as additional oil from sandstone cores. They mentioned that the right choice of nanoparticles also depends on the kind and nature of the inspected oil reservoir.

In order to measure the performance of microemulsion and its level of extraction efficiency on the IFT, Bera et al. (2014) investigated the effect of salinity on an anionic microemulsion through the water solubilization method. The study found that the microemulsion used efficiently reduces the IFT between the crude oil and brine. It is concluded that more than 25% of the original oil in place has been recovered after conventional water flooding. In another study, Bera et al. (2013) investigated the adsorption of surfactants onto the reservoir rock and the effect in performing a practical application of surfactant flooding. It has been found from their experiments that the adsorption of cationic surfactant on the sandstone surface is more than an anionic surfactant, while nonionic surfactant shows intermediate behavior. X-ray diffraction (XRD) and Fourier transform infrared spectroscopy (FTIR) have been used to determine the main components present in the sand particles and examine the interaction between them and surfactants tested before and after aging with a surfactant, respectively.

In this review, a comparison between ASP and nanoparticle flooding technologies will be explored in some detail then the recovery factor for some of these flooding techniques will be mentioned. Finally, an outlook on the difficulties and challenges of applying each technique will be



Figure 1. Classification of some major EOR processes (Olajire 2014).

demonstrated for optimum oil production. Figure 1 illustrates some of the general enhanced oil recovery (EOR) methods.

2. ASP projects

Currently, there are 32 global ASP projects in the world where 19 of them were applied in China alone. Table 1 shows typical costs per barrel for a standard ASP operation, and Figure 2 demonstrates the incremental oil recovery for 21 global projects and their average value and locations.

ASP flooding can be developed technically so that the oil recovered is 10% higher than polymer flooding and 20% higher than waterflooding. There are currently more than (83×10^8) tons of reserves that can be produced by injecting ASP flood from which over (14×10^8) tons of reserves can be extracted for Daqing oil field alone in China (Yang et al. 2019). ASP flooding has economic limitations due to the large volumes of chemicals injected. Therefore, the technical and economic feasibility of ASP flooding must be considered for the effective use of injected chemicals and slug formulation.

3. Effect of alkaline, surfactant, and polymer

There are different opinions about the alkaline used in ASP formulations. Some studies found that using strong alkali like caustic soda (NaOH) could significantly improve oil recovery (Zuo et al. 2012; Arvis et al. 2017). Other studies stated that using a weak base like sodium carbonate (Na₂CO₃) was more effective in recovering oil (Yin et al. 2017; Guo et al. 2018; Huang 2020). Yin et al. (2017) performed several experiments to obtain the optimal concentration of alkali that may lead to the best results. They observed that IFT decreased to a low value of 1.13 mN/m when using Na₂CO₃ at concentration 1.2 wt.%. This is achieved because Na₂CO₃ alkali has ions of

Slugs due to chemicals			
Unit	Main slug	Pre-flush	Post-flush
a-unit volume	0.308	0.097	0.242
%	1.25		
ppm	1350	1450	800
%	0.27		
USD per lb	1.03		
USD per lb	0.12		
USD per lb	2.2		
%OOIP	21.8		
USD per bbl	4.37	0.23	0.32
USD per bbl	4.93		
	Unit a-unit volume % ppm % USD per lb USD per lb WSD per lb %OOIP USD per bbl USD per bbl	Slugs due to o Unit Main slug a-unit volume 0.308 % 1.25 ppm 1350 % 0.27 USD per lb 1.03 USD per lb 0.12 USD per lb 2.2 %OOIP 21.8 USD per bbl 4.37 USD per bbl 4.93	Slugs due to chemicalsUnitMain slugPre-flusha-unit volume0.3080.097%1.25ppm13501450%0.27USD per lb1.03USD per lb0.12USD per lb2.2%OOIP21.8USD per bbl4.370.23USD per bbl4.93

Table 1. Chemical cost estimates for a standard protocol of ASP (Sheng 2014)



Figure 2. Incremental oil recovery for 21 worldwide ASP projects (Sheng 2014).

 OH^- that reacted with the molecules of petroleum acid (HA) found in the crude oil to produce the so-called "soap" or natural surfactant (A⁻) according to the following equation:

$$HA (acid) + OH^{-} \rightarrow A^{-}(Soap) + H_2O$$
(1)

Khan et al. (2009) performed an experimental investigation to find the best combination for ASP flooding. They tested two cores for this purpose. The first one is devoted to 0.1 wt.% sodium dodecyl sulfate (SDS) surfactant, 2000 ppm HPAM polymer and 0.7 wt.% NaOH alkali. The second core is used for 0.075 wt.% sodium dodecylbenzene sulfonate (SDBS), 2000 ppm HPAM and 0.7 wt.% NaOH. It was possible to recover an additional 24% OOIP from the first core and about 22% OOIP from the second one. The excess recovery has been achieved due to the significant interfacial tension reduction, which decreased to 30–35 mN/m compared to waterflooding (72 mN/m).

4. Application of nano-fluids in EOR

NPs have two unique properties that make them attractive for many industries. First, they have a small particle size (1-100 nm) which enables them 46 👄 A. ARSAD ET AL.

to transport to pores not accessible to large particles. Secondly, they have a large surface to volume ratio. When these two main benefits are combined, they can be effectively involved in many industries, not only EOR (Esfandyari Bayat et al. 2014; El-Diasty and Aly 2015; Oseh et al. 2020a, b).

Many researchers investigated TiO_2 polymeric nano-fluid (PNF), and an improvement in oil recovery was reported. Nonetheless, the data obtained is insufficient to authenticate TiO_2 NPs as an efficient additive for polymeric flooding. This is due to the titanium metal itself, which is listed as a transition metal. Besides that, TiO_2 NPs are classified to have variable oxidation. Hence, it is considered unstable.

 Al_2O_3 NPs is one of the most widely used NPs as well. High temperatures are found to have a small effect on fluids containing Al_2O_3 NPs. Moreover, Al_2O_3 NPs play an important key role in slowing down polymer's degradation upon effective shear forces. The existing oxygen atom in its chemical structure helps counter the cations found in saline water and can withstand in the saline environment.

5. Challenges for ASP flooding operations

Some challenges need to be faced with making ASP flooding a more efficient and economical process. First, to obtain a higher incremental recovery, the oil-water interfacial tension must reach a magnitude of 10-3 mN/m, which cannot be easily achieved depending on the surfactant concentration. Secondly, it was found that adding more alkali will help in reducing the interfacial tension to the ultra-low value (magnitude of 10^{-3} mN/m), but at the same time, this may lead to some problems like decreasing the viscosity of ASP solution. To fix this additional problem, a substantial amount of polymer is recommended to substitute for the decreasing viscosity. Moreover, adding a high alkali concentration may cause technical scaling problems in the piping system and instruments. Therefore, the alkali concentration must be tailored to an appropriate quantity to avoid these problems and reduce the utilization of the chemical.

6. Mechanisms of nano-fluid flooding

The implementation of nanoscale entity can increase oil recovery considerably through achieving the following:

- I. Enhancing the viscosity of fluid acting as an injectant and decreasing the oil viscosity.
- II. Decreasing the interfacial tension and improving the emulsion formation.
- III. Modifying the wettability from oil-wet to water-wet by decreasing the contact angle between the rock surface and oil.



Figure 3. Disjoining pressure gradient at oil-nano-fluid interface (Kazemzadeh et al. 2019).

IV. Diminishing the reservoir formation damage by reducing the chemicals adsorbed on the rock matrix.

NP suspension is determined through the regulation of electrostatic repulsion force between its particles. As the repulsion force becomes more prominent, the more stable will be the NPs suspension, and the NPs will not aggregate. Generally, three mechanisms have been proposed to explain the formation activity of NPs. The first theory is related to what is called the "disjoining pressure". This pressure prevents the fluid from sticking to the solid surface and it is the difference in pressure between the fine fluid layer and the fluid bulk. NPs make the interface between discontinuous fluids through this mechanism in the form of wedge film. The disjoining pressure is formed due to energies found in the Brownian motion of the particles and the electrostatic repulsion forces between them (El-Diasty and Aly 2015). Figure 3 shows the representation of this principle.

The second mechanism is called the "density difference". This process is correlated with the density difference between the water and NPs, which agglomerate at the entrant of the pore throats. This agglomeration permits the fluid to flow to the neighboring pores and causes the oil to move and be produced in the adjacent pores (El-Diasty and Aly 2015). The third mechanism is related to the wettability alteration and interfacial tension reduction. This mechanism explains that oil is recovered due to the wettability alteration from oil-wet to neutral or water-wet, and therefore the IFT will be reduced at the interface region between the oil and water. Figure 4 shows a schematic view of these three mechanisms.



Figure 4. EOR mechanisms of nano-fluids within the porous media (Ali et al. 2018).

The increase of salinity leads to nanoparticle agglomerating. However, increasing salt ions does not prevent the movement of NPs, but it facilitates the accumulation of NPs on the surfaces of the rock. The temperature also affects the NPs so that when the temperature increases, the NPs agglomeration begins, which diminishes its stability. Injection rate, from the other part, also effects on the performance of NPs. Small molecules of water move at a high injection rate faster than suspended NPs and this leads a high injection rate faster than suspended NPs, leading to the agglomeration of NPs, which block the pore throats and cause the decrease of oil recovery. Table 2 summarizes some previous studies on the application of NPs in EOR experiments.

Polymers may be added to the injected water to increase its viscosity. Therefore, polymer flooding can be considered as one of the most prevalent chemical operations of EOR. The injection of polymer solutions will minimize water mobility, increase sweeping performance, and recover more oil (Ogolo et al. 2012). The primary polymers injected in chemical flooding include PAM, HPAM, xanthan gum, biopolymers (Zolfaghari et al. 2006; Hu et al. 2017).

7. Nanoparticles in oil recovery

Agi et al. (2019) synthesized crystalline starch NPs (CSNP) from plant and fruit extracts using weak ascorbic acid. The rheological formation of CSNP

Seq.	Author	Method	Receiver rock	Scope of work
1	Agi et al. (2019)	Core flooding	Sandstone	Synthesizing crystalline starch nanoparticles from plant and fruits extracts and by using weak ascorbic acid and comparing the performance of manufactured NPs with native cassava starch and polymer xanthan
2	Aminzadeh Goharrizi (2013)	Core flooding	Boise sandstone	Multi-phase displacement experimental calculation of the sweep efficiency with NPs
3	Cheraghian et al. (2017)	Core flooding		Improvement of oil recovery through the application of TiO ₂ polymeric nanofluid (PNF)
4	Assef et al. (2016)	Core flooding	Sandstone	Controlling the colloidal and porous media's interactions during low-salinity flooding of water and alkaline MgO NPs
5	Cheraghian et al. (2014)	Core flooding		Evaluating the addition of nano- clay to improve the rheology properties of polyacrylamide solutions used in enhanced oil recovery
6	Bagaria et al. (2013)	Chemical method		Weakly adsorbed nano-silica and Iron oxides NPs grafted in concentrated salt at high temperatures with sulfonated copolymers
7	Greff and Babadagli (2011)	Thermal		Nano-sized metal ion 's catalytic impact in asphalt molecules during heavy oil thermal recovery
8	Huang and Clark (2015)	Core flooding		Improvement of oil recovery with specified NPs through the control of migration from sources to reservoirs by flooding
9	Cieśliński and Krygier (2014)	Contact angle	Plates made of glass	Water–TiO ₂ , water–Al ₂ O ₃ , and water–Cu nanofluids increase critical heat flux
10	Ehtesabi et al. (2015)	Core flooding		Evaluating the deposition during transport in the core plug by TiO ₂ NPs in the recovery of heavy oil
11	Kazemzadeh et al. (2015)	Interfacial tension		Impact of Fe ₃ O ₄ nanoparticles on asphaltene precipitation during CO ₂ injection
12	Hamedi-Shokrlu and Babadagli (2014)	Micromodel		Stabilization and interaction of nonmetal catalysts with an oleic phase during EOR in porous media
13	Zhang et al. (2010)	Emulsion		NP with stabilized emulsions applications in FOR
14	Mintsa et al. (2009)	Thermal		New thermal conductivity data for water-based nanofluids contingent on temperatures
15	Khalilinezhad et al. (2017)	Core flooding		Checking the influence on heavy oil recovery during the flooding of hydrophilic nanosilica
16	Li et al. (2013)	Adsorption and wettability	Berea sandstone	Influence of adsorption of nanosilica on Berea sandstone wettability index
				(continued)

Table 2. A summary of some studies for EOR processes using nanofluids

(continued)

50 👄 A. ARSAD ET AL.

Tabl	Table 2. Continued						
Seq.	Author	Method	Receiver rock	Scope of work			
17	Kjøniksen et al. (2008)	Chemical method		Modified polysaccharides application in EOR			
18	Singh and Mohanty (2015)	Core flooding	Berea sandstone	The synergy between surfactants and NPs in foams stabilization for EOR			
19	Shokrlu and Babadagli (2014)	Thermal		The reduction in viscosity of heavy oil and bitumen in aqueous and non-aqueous thermal applications by micro- nano metal particles			
20	Skauge et al. (2010)	Core flooding	Berea sandstone	NPs for EOR			
21	Zhang et al. (2014)		Berea sandstone	NP dispersions for EOR: mechanism and experiment with imbibition			
22	Youssif et al. (2018)	Core flooding	Sandstone	Assessing the impact on oil recovery of nanosilica			
23	Vafaei et al. (2008)	Contact angle	Glass and silicon wafers	NPs impact on contact angle through the sessile droplet method			
24	Shamsi Jazeyi et al. (2014)	Chemical method		Coated NPs with polymer for EOR			

performance was compared with native cassava starch (CS) and polymer xanthan. Three techniques were adopted in performing CSNP in extracting oil. These techniques include weak-acid hydrolysis, ultrasonic treatment, and nano-precipitation. These techniques were found satisfactory in producing polygonal and spherical NPs with an average diameter of 100 nm. The concentration, morphology, and surface charge of the solution are the main factors that affected the rheology of the system produced.

Their study stated that the viscosity of NPs solutions increases with the increase of NPs surface area and the increased temperature of CS and CSNP. In contrast, the viscosity of the solution decreases with the increased temperature of polymer xanthan. Figure 5 shows a TEM analysis for CSNP produced.

8. Prospects for efficient ASP and nano-fluid flooding

Since 2014, ASP flooding in Daqing Oilfield in China has officially started its commercial production and oil produced in 2015 was about 3.5 million tons. The quantity of oil produced by this technique was approximately 9% of total production for that oilfield. Despite that, ASP flooding has some limitations in field applications due to the large volumes of chemicals injected. The technical feasibility of ASP flooding depends mainly on the economical use of injected chemicals.

ASP flooding is applied after the reservoir has been water flooded or polymer flooded for a long time. Most oil reservoirs contain gas-phase trapped in between the rock's matrix. In areas where gas flaring is not allowed and no modern infrastructure deals with gas transportation, the



Figure 5. TEM image of CSNP (a) platy and pear-like structure, (b) evenly distributed spherical crystals, (c) nucleation due to cavitation bubbles, (d) secondary nucleation and crystal growth (Agi et al. 2019).

reinjection of the produced gas may be the final possible solution. Nonetheless, no precise data are available in the literature about the direct influence of in situ gas (trapped or continuous) on the performance of ASP flooding.

Low concentrations of alkali and surfactant is considered enough to achieve low interfacial tension between oil and water. From another aspect, ASP flooding is considered as an expensive operation, and an optimization approach has to be performed before commencing with the production operation. To maintain an economic operation, this is considered necessary to account for all controlling variables, including oil prices. Therefore, extensive laboratory floods, approximate numerical simulations, and pilot tests must be operated before moving to the commercial production level.

Although NPs floods have shown significant benefits in laboratory scale in extracting more oil, the drawbacks concerns cannot be ignored. One of these drawbacks is the high cost of manufacturing NPs and their compatibility to be operated under actual reservoir conditions. Generally, the synthesis and managing operation in EOR process can be costly and large injection volumes of NPs may be required. Besides that, each oilfield's

52 👄 A. ARSAD ET AL.

Used nanoparticles	Application	Location	Results	References
Aluminum oxide nano-silica	Inhibition and remediation of formation damage	Columbia	After 8 months of injecting aluminum oxide, the oil rate has increased by 300 bbl/day. Another trial using nano-silica resulted in an oil rate increase of 134 bbl/day.	Franco et al. (2017)
Carbon-based fluorescent nanoparticle named "A-Dots"	Evaluating the stability of nanoparticles in harsh formation environment as water injection tracers	Saudi Arabia	The results showed a high recovery percentage up to 86% suggesting their high stability.	Kanj et al. (2011), Kosynkin and Alaskar (2016)
Unnamed	Enhancing the mobility ratio of heavy oils	Columbia	An immediate increase in the oil production rate was observed along with a reduction of 11% in the basic sediment and water.	Zabala et al. (2016)
Unnamed	Stabilizing shale formation using water-based drilling fluid containing nanoparticles	Brazil	The results showed good performance in terms of shale hydration inhibition and wellbore stability. The same fluid was stored and used to drill another section in a different well after almost 3 months, which resulted in a 15% reduction in the well cost.	Barroso et al. (2018)

Table 3. Summary of reported nanofluids field trials

conditions and unique properties may not be suitable for certain NPs which in turn add, each oilfield's conditions and unique properties may not be suitable for specific NPs, which adds more challenges to this issue. High temperature and salinity conditions in some formations may decrease the efficacy of the NPs as these environments can be destructive for NPs structures. It is worth mentioning that only a few field trials have been reported in the literature. A summary of field trials for nanoparticles and nano-fluids are given in Table 3.

9. Conclusions

This study shed light on essential technologies involved in EOR processes: ASP and nano-fluid flooding. The recovery criteria depend on wettability alteration of the rock surface from oil-wet to water-wet and reduction in IFT between the oil and water phases. The increase in the macroscopic displacement efficiency and the decrease in mobility ratio between the water and the oil also significantly increase oil recovery. Despite that, ASP flooding has some limitations in field applications due to the large volumes of chemicals injected. The technical feasibility of ASP flooding depends mainly on the economical use of injected chemicals. Nano-fluid flooding has been applied as a pilot process in some countries like China, Saudi Arabia, and Columbia and showed promising results in enhancing oil recovery. Many flooding experiments have revealed that NPs can reduce the IFT and the contact angle between the oil and rock surface. NPs are mixed with polymers, surfactants and alkalis to improve recovery and reduce chemicals in the injection stream. NPs suspension and its stability in any fluid are determined by the electrostatic repulsion forces between its material particles. If the repulsion forces are big enough, the suspended NPs become more stable and will not aggregate. The inclusion of NPs in chemical agents like polymer can significantly increase the recovery ratio.

Although NPs floods have shown significant benefits in laboratory scale in extracting more oil, the drawbacks concerns cannot be ignored. One of these drawbacks is the high cost of manufacturing NPs and their compatibility under natural reservoir conditions. It is found that nanoparticles are effective to recover at least 10% additional oil from sandstone cores. The right choice of nanoparticles in EOR operations also depends on the kind and nature of the oil reservoir being inspected. The future work of NPs applications should address the following gaps: the accurate capture of aging time of NPs in the base fluid and the exploring of balance between the rock surface and NPs charge while maintaining their effectiveness as interfacial tension modifiers.

Authorship contribution statement

Agus Arsad: Conceptualization, Resources, Supervision, Validation, Writing – review and editing, Visualization, Hasanain A. Al-Jaber: Conceptualization, Information and data collection, Formal analysis, Writing – original draft, Radzuan Junin: Supervision, Methodology, Project administration, Funding acquisition, Sulalit Bandyopadhyay: Supervision, Data curation, Writing – review and editing, Abdulmunem R. Abdulmunem: Formal analysis, Writing – review and editing, Investigation, Jeffrey Onuoma Oseh: Writing – review and editing, Data curation, Agi Augustine: Writing – review and editing, Resources, Muslim Darbi Abdurrahman: Funding acquisition, Evizal Abdul Kadir: Funding acquisition, Sharul Kamal Abdul Rahim: Funding acquisition.

Conflict of interest

The authors would like to declare that there is no potential conflict of interest during the preparation of this paper.

Acknowledgments

The authors would like to express their high appreciation for the financial support received from the School of Chemical and Energy Engineering, Universiti Teknologi Malaysia (UTM) through Grant No. R.J130000.7351.4B549 and Q.J130000.3551.07G11.

ORCID

Agus Arsad D http://orcid.org/0000-0002-0111-1939 Abdulmunem R. Abdulmunem D http://orcid.org/0000-0001-6954-3546 Jeffrey Onuoma Oseh D http://orcid.org/0000-0003-4287-7591

References

- Agi, A., R. Junin, A. Gbadamosi, A. Abbas, N. B. Azli, and J. Oseh. 2019. Influence of nanoprecipitation on crystalline starch nanoparticle formed by ultrasonic assisted weak-acid hydrolysis of cassava starch and the rheology of their solutions. *Chemical Engineering and Processing Process Intensification* 142:107556–16. doi:10.1016/j.cep. 2019.107556.
- Ali, J. A., K. Kolo, A. K. Manshad, and A. H. Mohammadi. 2018. Recent advances in application of nanotechnology in chemical enhanced oil recovery: Effects of nanoparticles on wettability alteration, interfacial tension reduction, and flooding. *Egyptian Journal of Petroleum* 27 (4):1371–83. doi:10.1016/j.ejpe.2018.09.006.
- Aminzadeh, B., D. H. Chung, X. Zhang, S. L. Bryant, C. Huh, and D. A. DiCarlo. 2013. Influence of surface-treated nanoparticles on displacement patterns during CO² injection SPE Annual Technical Conference and Exhibition. doi: 10.2118/166302-MS.
- Arvis, A., S. Le Van, and B. H. Chon. 2017. Feasibility study of alkali-surfactant-polymer flooding on enhancing heavy-oil recovery in a heterogeneous thin reservoir. *International Journal of Applied Engineering Research* 12 (18):7225–37.
- Assef, Y., P. Pourafshary, and H. Hejazi. 2016. Controlling interactions of colloidal particles and porous media during low salinity water flooding and alkaline flooding by MgO Nanoparticles. Society of Petroleum Engineers – SPE EOR Conference at Oil and Gas West Asia: 179768. doi: 10.2118/179768-MS.
- Bagaria, H. G., Z. Xue, B. M. Neilson, A. J. Worthen, K. Y. Yoon, S. Nayak, V. Cheng, J. H. Lee, C. W. Bielawski, and K. P. Johnston. 2013. Iron oxide nanoparticles grafted with sulfonated copolymers are stable in concentrated brine at elevated temperatures and weakly adsorb on silica. ACS Applied Materials & Interfaces 5 (8):3329–39. doi: 10.1021/ am4003974.
- Barroso, A. L., C. P. Marcelino, A. B. Leal, D. M. Odum, C. Lucena, M. Masculo, and F. Castro. 2018. New generation nano technology drilling fluids application associated to geomechanic best practices: Field trial record in bahia Brazil. *Proceedings of the Annual Offshore Technology Conference*. 6: 4542–4553.
- Bayat, E., A. R. Junin, A. Samsuri, A. Piroozian, and M. Hokmabadi. 2014. Impact of metal oxide nanoparticles on enhanced oil recovery from limestone media at several temperatures. *Energy & Fuels* 28 (10):6255–66. doi: 10.1021/ef5013616.
- Bera, A., S. Shah, M. Shah, J. Agarwal, and R. K. Vij. 2020. Mechanistic study on silica nanoparticles-assisted guar gum polymer flooding for enhanced oil recovery in sandstone reservoirs. *Colloids and Surfaces A: Physicochemical and Engineering Aspects* 598:124833. doi:10.1016/j.colsurfa.2020.124833.
- Bera, A., and H. Belhaj. 2016. Application of nanotechnology by means of nanoparticles and nano-dispersions in oil recovery – A comprehensive review. *Journal of Natural Gas Science and Engineering* 34:1284–309. doi:10.1016/j.jngse.2016.08.023.
- Bera, A., T. Kumar, K. Ojha, and A. Mandal. 2014. Screening of microemulsion properties for application in enhanced oil recovery. *Fuel* 121:198–207. doi:10.1016/j.fuel.2013.12.051.

- Bera, A., T. Kumar, K. Ojha, and A. Mandal. 2013. Adsorption of surfactants on sand surface in enhanced oil recovery: Isotherms, kinetics and thermodynamic studies. *Applied Surface Science* 284:87–99. doi:10.1016/j.apsusc.2013.07.029.
- Cheng, J., W. Zhou, Q. Wang, G. Cao, W. Bai, C. Zhao, and M. Luo. 2014. Technical breakthrough in production engineering ensures economic development of ASP flooding in daqing oilfield. Society of Petroleum Engineers – SPE Asia Pacific Oil and Gas Conference and Exhibition, APOGCE 2014, Changing the Game: Opportunities, Challenges and Solutions 2:941–50.
- Cheraghian, G., S. S. Khalili Nezhad, M. Kamari, M. Hemmati, M. Masihi, and S. Bazgir. 2014. Adsorption polymer on reservoir rock and role of the nanoparticles, clay and SiO₂. *International. Nano Letters* 4 (3):1–8.
- Cheraghian, G., S. S. Khalili Nezhad, M. Kamari, M. Hemmati, M. Masihi, and S. Bazgir. 2014. Adsorption polymer on reservoir rock and role of the nanoparticles, clay and SiO₂. *International. Nano Letters* 4 (3):1–8.
- Cheraghian, G., S. Rostami, and M. Afrand. 2020. Nanotechnology in enhanced oil recovery. *Processes* 8 (9):1073. doi:10.3390/pr8091073.
- Cheraghian, G., S. Kiani, N. N. Nassar, S. Alexander, and A. R. Barron. 2017. Silica nanoparticle enhancement in the efficiency of surfactant flooding of heavy oil in a glass micromodel. *Industrial and Engineering Chemistry Research* 56 (30):8528–34. doi:10. 1021/acs.iecr.7b01675.
- Cheraghian, G., and S. Tardasti. 2012. Improved oil recovery by the efficiency of nano-particle in imbibition mechanism. 74th European Association of Geoscientists and Engineers Conference and Exhibition 2012 Incorporating SPE EUROPEC 2012: Responsibly Securing Natural Resources cp-:315-00078.
- Cieliski, J. T., and K. Krygier. 2014. Augmentation of the Critical Heat Flux in Water-Al₂O₃, Water-TiO₂ and water-Cu Nanofluids. *MATEC Web of Conferences*. 18: 01012.
- Ehtesabi, H., M. Mahdi Ahadian, and V. Taghikhani. 2015. Enhanced heavy oil recovery using TiO₂ nanoparticles: Investigation of deposition during transport in core plug. *Energy & Fuels* 29 (1):1–8. doi: 10.1021/ef5015605.
- El-Diasty, A. I., and A. M. Aly. 2015. Understanding the mechanism of nanoparticles applications in enhanced oil recovery. Society of Petroleum Engineers. SPE North Africa Technical Conference and Exhibition 2015, NATC 2015, 944–962. doi:10.2118/175806-MS.
- Esfandyari Bayat, A., R. Junin, A. Samsuri, A. Piroozian, and M. Hokmabadi. 2014. Impact of metal oxide nanoparticles on enhanced oil recovery from limestone media at several temperatures. *Energy & Fuels* 28 (10):6255–66. doi:10.1021/ef5013616.
- Franco, C. A., Z. Richard, and F. B. Cortés. 2017. Nanotechnology applied to the enhancement of oil and gas productivity and recovery of Colombian fields. *Journal of Petroleum Science and Engineering* 157:39–55. doi: 10.1016/j.petrol.2017.07.004.
- Gbadamosi, A. O., R. Junin, M. A. Manan, A. Agi, J. O. Oseh, and J. Usman. 2019. Synergistic application of aluminium oxide nanoparticles and oilfield polyacrylamide for enhanced oil recovery. *Journal of Petroleum Science and Engineering* 182:106345–17. doi: 10.1016/j.petrol.2019.106345.
- Greff, J., and T. Babadagli. 2011. Catalytic effects of nano-size metal ions in breaking asphaltene molecules during thermal recovery of heavy-oil. *SPE Annual Technical Conference and Exhibition*. doi: 10.2118/146604-MS.
- Guo, H., Y. Li, F. Wang, and Y. Gu. 2018. Comparison of strong-alkali and weak-alkali ASP-flooding field tests in Daqing oil field. *SPE Production and Operations* 33 (02): 353–62. doi:10.2118/179661-PA.

56 👄 A. ARSAD ET AL.

- Hamedi-Shokrlu, Y., and T. Babadagli. 2014. Stabilization of nanometal catalysts and their interaction with oleic phase in porous media during enhanced oil recovery. *Industrial & Engineering Chemistry Research* 53 (20):8464–75. doi: 10.1021/ie4042033.
- Huang, M. 2020. Recovery characteristics of weak alkali ASP flooding in second oil reservoir. *IOP Conference Series: Earth and Environmental Science* 446:052057
- Huang, T., and D. E. Clark. 2015. Enhancing oil recovery with specialized nanoparticles by controlling formation- Fines migration at their sources in waterflooding reservoirs. SPE Journal 20 (04):743–6. doi: 10.2118/166294-PA.
- Hu, Z., M. Haruna, H. Gao, E. Nourafkan, and D. Wen. 2017. Rheological properties of partially hydrolysed polyacrylamide seeded by nanoparticles. *Industrial and Engineering Chemistry Research* 56 (12):3456–63. doi:10.1021/acs.iecr.6b05036.
- Kanj, M. Y., M. H. Rashid, and E. P. Giannelis. 2011. Industry first field trial of reservoir nanoagents. SPE Middle East Oil and Gas Show and Conference MEOS, Proceedings. 3: 1883–92.
- Kazemzadeh, Y., B. Dehdari, Z. Etemadan, M. Riazi, and M. Sharifi. 2019. Experimental investigation into Fe₃O₄/SiO₂ nanoparticle performance and comparison with other nanofluids in enhanced oil recovery. *Petroleum Science* 16 (3):578–90. doi: 10.1007/ s12182-019-0314-x.
- Kazemzadeh, Y., S. Shojaei, M. Riazi, and M. Sharifi. 2019. Review on application of nanoparticles for EOR purposes: A critical review of the opportunities and challenges. *Chinese Journal of Chemical Engineering* 27 (2):237–46. doi:10.1016/j.cjche.2018.05.022.
- Khademolhosseini, R., A. Jafari, S. M. Mousavi, M. Manteghian, and Z. Fakhroueian. 2020. Synthesis of silica nanoparticles with different morphologies and their effects on enhanced oil recovery. *Applied Nanoscience* 10 (4):1105–14. doi: 10.1007/s13204-019-01222-y.
- Khalilinezhad, S. S., G. Cheraghian, E. Roayaei, H. Tabatabaee, and M. S. Karambeigi. 2017. Improving heavy oil recovery in the polymer flooding process by utilizing hydrophilic silica nanoparticles. *Energy Sources, Part A: Recovery, Utilization and Environmental Effects* :1–10. doi: 10.1080/15567036.2017.1302521.
- Khan, M. Y., A. Samanta, K. Ojha, and A. Mandal. 2009. Design of alkaline/surfactant/ polymer (ASP) slug and its use in enhanced oil recovery. *Petroleum Science and Technology* 27 (17):1926–42. doi:10.1080/10916460802662765.
- Kjøniksen, A. L., N. Beheshti, H. K. Kotlar, K. Zhu, and B. Nyström. 2008. Modified polysaccharides for use in enhanced oil recovery applications. *European Polymer Journal* 44 (4):959–67. doi: 10.1016/j.eurpolymj.2008.01.028.
- Kosynkin, D., and M. Alaskar. 2016. Oil industry first interwell trial of reservoir nanoagent tracers. Proceedings SPE Annual Technical Conference and Exhibition: 181551.
- Li, S., Y. Li, L. Zhang, and Z. Miao. 2013. Application of real-time polymerase chain reaction (PCR) in detection of microbial aerosols. *Environmental Forensics* 14 (1):16–9. doi: 10.1080/15275922.2012.760180.
- Mintsa, H. A., G. Roy, C. T. Nguyen, and D. Doucet. 2009. New temperature dependent thermal conductivity data for water-based nanofluids. *International Journal of Thermal Sciences* 48 (2):363–71. doi: 10.1016/j.ijthermalsci.2008.03.009.
- Mokhatab, S., M. A. Fresky, and M. R. Islam. 2006. Applications of nanotechnology in oil and gas. *Journal of Petroleum Technology* 58 (04):48–51. doi: 10.2118/0406-0048-JPT.
- Nazari Moghaddam, R., A. Bahramian, Z. Fakhroueian, A. Karimi, and S. Arya. 2015. Comparative study of using nanoparticles for enhanced oil recovery: Wettability alteration of carbonate rocks. *Energy & Fuels* 29 (4):2111–9. doi: 10.1021/ef5024719.

- Ogolo, N. A., O. A. Olafuyi, and M. O. Onyekonwu. 2012. Enhanced oil recovery using nanoparticles. Society of Petroleum Engineers SPE Saudi Arabia Section Technical Symposium and Exhibition 2012, 276–284. doi:10.2118/160847-MS.
- Olajire, A. A. 2014. Review of ASP EOR (alkaline surfactant polymer enhanced oil recovery) technology in the petroleum industry: Prospects and challenges. *Energy* 77:963–82. doi:10.1016/j.energy.2014.09.005.
- Oseh, J. O., M. N. A. Mohd Norddin, I. Ismail, A. O. Gbadamosi, A. Agi, and A. R. Ismail. 2020a. Experimental investigation of cuttings transportation in deviated and horizontal wellbores using polypropylene-nanosilica composite drilling mud. *Journal of Petroleum Science and Engineering* 189:106958–24. doi:10.1016/j.petrol.2020.106958.
- Oseh, J. O., M. N. A. M. Norddin, H. N. Muhamad, I. Ismail, A. O. Gbadamosi, A. Agi, A. R. Ismail, and S. O. Blkoor. 2020b. Influence of (3-aminopropyl) triethoxysilane on entrapped polypropylene at nano-silica composite for shale swelling and hydration inhibition. *Journal of Petroleum Science and Engineering* 194:107560–16. doi:10.1016/j.petrol. 2020.107560.
- Shamsijazeyi, H., C. A. Miller, M. S. Wong, J. M. Tour, and R. Verduzco. 2014. Polymercoated nanoparticles for enhanced oil recovery. *Journal of Applied Polymer Science* 131 (15). doi: 10.1002/app.40576.
- Sheng, J. J. 2014. A comprehensive review of alkaline-surfactant-polymer (ASP) flooding. Asia-Pacific Journal of Chemical Engineering 9 (4):471–489. doi:10.1002/apj.1824.
- Singh, R., and K. K. Mohanty. 2015. Synergy between nanoparticles and surfactants in stabilizing foams for oil recovery. *Energy & Fuels* 29 (2):467–79. [Database] doi: 10.1021/ ef5015007.
- Skauge, T., K. Spildo, and A. Skauge. 2010. Nano-sized particles for EOR. Proceedings SPE Symposium on Improved Oil Recovery. 2: 1281–90.
- Vafaei, M. T., R. Eslamloueyan, L. Enfeali, and S. Ayatollahi. 2009. Analysis and simulation of steam distillation mechanism during the steam injection process. *Energy & Fuels* 23 (1):327–33. doi: 10.1021/ef800602w.
- Yang, P., Z. A. Li, B. Xia, Y. J. Yuan, Q. T. Huang, W. L. Liu, and C. Y. Cheng. 2019. Comprehensive review of alkaline-surfactant-polymer (ASP)-enhanced oil recovery (EOR). Springer Series in Geomechanics and Geoengineering 216039:858–72.
- Yin, D., D. Zhao, J. Gao, and J. Gai. 2017. Experimental study of enhancing oil recovery with weak base alkaline/surfactant/polymer. *International Journal of Polymer Science* 2017 (4):1–7. doi:10.1155/2017/4652181.
- Youssif, M. I., R. M. El-Maghraby, S. M. Saleh, and A. Elgibaly. 2018. Silica nano-fluid flooding for enhanced oil recovery in sandstone rocks. *Egyptian Journal of Petroleum* 27 (1):105–10. doi:10.1016/j.ejpe.2017.01.006.
- Zabala, R., C. A. Franco, and F. B. Cortés. 2016. Application of nano-fluids for improving oil mobility in heavy oil and extra-heavy oil: A field test. SPE – DOE Improved Oil Recovery Symposium Proceedings, 2016 January.
- Zhang, H., A. Nikolov, and D. Wasan. 2014. Enhanced oil recovery (EOR) using nanoparticle dispersions: Underlying mechanism and imbibition experiments. *Energy & Fuels* 28 (5):3002–9. doi: 10.1021/ef500272r.
- Zhang, T., Davidson, D., and S. L. Bryant, 2010. and C. Huh. Nanoparticle-stabilized emulsions for applications in enhanced oil recovery. *SPE Improved Oil Recovery Symposium* 129885.
- Zolfaghari, R., A. A. Katbab, J. Nabavizadeh, R. Y. Tabasi, and M. H. Nejad. 2006. Preparation and characterisation of nanocomposite hydrogels based on polyacrylamide

58 👄 A. ARSAD ET AL.

for enhanced oil recovery applications. *Journal of Applied Polymer Science* 100 (3): 2096–103. doi:10.1002/app.23193.

Zuo, X., S. Li, W. Li, R. Song, T. Wang, and H. Xu. 2012. A study on the remaining oil after strong base ASP flooding. SPE Annual Technical Conference and Exhibition: 159675

Nomenclature

IFT Interfacial tension, mN/m

Abbreviations

EOR	Enhanced oil recovery
ASP	Alkali-surfactant-polymer
SP	Surfactant polymer
NPs	Nanoparticles
OOIP	Original oil in place
HPAM	Partially hydrolyzed polyacrylamide PAMpolyacrylamide
PNF	Polymeric nano-fluid
SDS	Sodium dodecyl sulfate
SDBS	Sodium dodecyl benzene sulfonate
TEM	Transmission electron microscopy
CFD	Computational fluid dynamics
CSNP	Crystalline starch Nanoparticles
CSNF	Crystalline starch Nano-fluid
CS	Cassava starch

