

Anas Puri <anaspuri@eng.uir.ac.id>

### 355034410364791593: A/Prof. Anas Puri: International Journal of GEOMATE

**geomate** <noreply@jotform.com> Reply-To: zakaria@bio.mie-u.ac.jp To: anaspuri@eng.uir.ac.id

Dea A/Prof. Anas Puri,

Thanks. Your Paper ID is 355034410364791593. Your short ID is last 5 digits. Pls use this short ID for further communication. We would get back to you with review results as early as possible.

Best regards.

### 

Dr. Zakaria Hossain (Ph.D. Kyoto University),

Editor-in-Chief, International Journal of GEOMATE (Geotechnique, Construction Materials and Environment) Professor, Mie University, Japan

E-mail: editor@geomatejournal.com Tel & Fax: +81-59-231-9578

Your submission details:	
Question	Answer
GEOMATE Conference ID number (If you have any)	6577
Title/Position	A/Prof.
Full Name	Anas Puri
University/Institute or Company Name	Islamic University of Riau
Office Address	Street Address: Jl. Kaharuddin Nasution 113 City: Pekanbaru State / Province: Riau Postal / Zip Code: 28284 Country: Indonesia
Phone Number	(761) 7047726

Tue, Nov 15, 2016 at 10:53 PM

E-mail	anaspuri@eng.uir.ac.id
Co-authors E-mail (separated by comma)	bbsuhendro@yahoo.com
Paper Title	EFFECTS OF VERTICAL WALL BARRIER ON THE RIGID PAVEMENT DEFLECTION OF FULL SCALE 1-PILE ROW NAILED-SLAB SYSTEM ON SOFT SUB GRADE
Research Area	Geotechnique
Recommend Reviewer-1 (E-mail, affiliation & address)	Reviewed during conference
Recommend Reviewer-2 (name E-mail & affiliation)	Reviewed during conference
Type of Paper	Original Paper
Upload File	GEOMATE-Effect of vertical wall barrier-final1.docx



Anas Puri <anaspuri@eng.uir.ac.id>

### Journal Publication-Resending (GEOMATE2016 Bangkok)

7 messages

**Zakaria** <zakaria@bio.mie-u.ac.jp> To: conference@geomate.org Thu, Nov 24, 2016 at 11:28 AM

Dear Authors,

Good afternoon. Regarding conf. paper reprint in journal, we are resending the following information. If you agree, then please follow the following procedure.

### Procedure:

1. Please read journal guideline (40% discount journal fees).

http://www.geomatejournal.com/submission-guidlines

- 2. Paper should be rewritten with journal template
- 3. ABSTRACT: Heading should be left alignment for journal (please see template).
- 4. Numbering in HEADINGS: All HEADINGS, subheading should be numbered for journal (please see template).
- 5. Please pay 360USD (must write conference ID during payment) using:

http://www.geomatejournal.com/payment

5. Submit journal copyright signed by all authors

6. Paper submit online (in "Reviewers Name": Please write as "Reviewed during conference"): Must write conference ID at ID section.

http://www.geomatejournal.com/paper-submission

- 7. Journal paper submission and payment deadline: November 30, 2016
- 8. Journal fees will be refunded fully if it is rejected finally.

Please always refer your ID in any communication to us.

Best regards.

Editor-in-Chief

Int. J. GEOMATE

\_\_\_\_\_

Dr. Zakaria Hossain (Ph.D. Kyoto Univ.)

Professor, Mie University, Japan

Editor-in-Chief, Int. J. of GEOMATE

editor@geomatejournal.com



Anas Puri <anaspuri@eng.uir.ac.id>

### Journal Paper Publication Fees: 6577: A/Prof.: ANAS PURI: GEOMATE All Payments: Auto Responder 1 message

geomate <noreply@jotform.com> Reply-To: editor@geomatejournal.com To: anaspuri@eng.uir.ac.id

Tue, Nov 29, 2016 at 9:38 AM

Dear A/Prof.ANAS PURI,

Thanks. Your fees has been received. We would take necessary action as early as possible.

Best regards.

**GEOMATE Secretary** 

Journal Paper Publication I Responder	Fees: 6577: A/Prof.: ANAS PURI: GEOMATE All Payments: Auto
Question	Answer
Item	Journal Paper Publication Fees
ID or Ref. or Item details above (if any)	6577
	<ul> <li>100 USD (Amount: 100.00 USD, Quantity: 3)</li> <li>50 USD (Amount: 50.00 USD, Quantity: 2)</li> <li>10 USD (Amount: 10.00 USD, Quantity: 1)</li> </ul>
	Total: \$410.00
Amount and Quantity	==Payer Info== First Name Anas Last Name Puri E-Mail anaspuri@yahoo.com
	==Address==
	Name Anas Puri

	Street City State Zip Country	Pascasarjana Universitas Islam Riau Gedung A Jl. Kaharuddin Nasution 113 Pekanbaru RIAU 28284 Indonesia		
Title/Position	A/Prof.			
Full Name	ANAS PURI			
University/Company	Islamic University of Riau			
Address	Street Address: Perum Yepupa Utama Permai Blok A7 City: Pekanbaru State / Province: Riau Postal / Zip Code: 28284 Country: Indonesia			
E-mail	anaspuri@	eng.uir.ac.id		

### EFFECTS OF VERTICAL WALL BARRIER ON THE RIGID PAVEMENT DEFLECTION OF FULL SCALE 1-PILE ROW NAILED-SLAB SYSTEM ON SOFT SUB GRADE

\*Anas Puri<sup>1</sup>, Bambang Suhendro<sup>2</sup>, Ahmad Rifa'i<sup>3</sup>

<sup>1</sup>Faculty of Engineering, Islamic University of Riau, Indonesia <sup>2, 3</sup> Faculty of Engineering, Gadjah Mada University, Indonesia

\*Corresponding Author, Received: 12 July 2016, Revised: 26 July 2016, Accepted: 29 Nov. 2016

**ABSTRACT:** The weaker part of rigid pavement when it is loaded is the edge of slab. Vehicle wheels that are often running in/out from/to pavement can cause void in the sub base-pavement interface for a long time loading period. Flexural moment caused by temperatures also precipitate the damages of pavement edge. To avoid the damage of pavement edge, the vertical wall barrier is added. This research is aimed to learn the contribution of vertical wall barrier on the pavement of Nailed-slab System to reduce the slab deflection. Full scale observation was done over models in soft clay soil. The full scale of 1 pile row Nailed-slab System was conducted on soft clay which consisted of 6.00 m x 1.20 m slab area with 0.15 m in slab thickness, 5 short micro piles as slab stiffeners which were installed under the slab. Piles and slab were connected monolithically, then in due with vertical concrete wall barrier on the two ends of slab. The system was loaded by compression loadings on the slab. Deflection of model without vertical wall barrier was analyzed by finite element method. Results show that the vertical wall barrier cannot significantly reduce the deflection for edge loading. It is to be expected that numerical application program could not model the vertical wall barrier which lower position than slab level.

Keywords: rigid pavement, soft clay, Nailed-slab System, vertical wall barrier, deflection

### 1. INTRODUCTION

The edge of a rigid pavement is the weaker part in bearing the traffic load. This part tends to get maximum deflection and to damage the pavement such as broken pavement, developed voids between sub grade and pavement, and can be followed by pumping. The edge of rigid pavement is also the weaker part in the Nailed-slab System [1]. Hence, in this research the edge of the pavement is reinforced by a vertical wall barrier. Furthermore, the behavior of Nailed-slab System and the contributions of vertical wall barrier will be studied.

A vertical wall barrier is usually reinforced concrete that is 10 cm - 20 cm in thickness and it is conducted in a vertical position that is 40 cm - 50 cm in height. Figure 1 shows an example of a vertical wall barrier. Another shape was used by The Indonesian Research and Development Center for Highway and Bridge [2]. Some benefits of a vertical wall barrier are [3]: (1) it acts as a slab stiffener for edge of pavement because this part will be a weaker part of pavement, (2) to avoid the void between sub grade and pavement due to the effect of the tires which often exit/ enter to/ from pavement, (3) to reduce the disturbing on berm,

and (4) as a vertical wall barrier to isolate the negative effects of water changing in sub grade. It prevents the water infiltration to the soil under the pavement slab.



Fig. 1 An example of vertical wall barrier

Puri, et.al. [1] conducted the 1-pile row Nailedslab model tests on the soft clay to learn the effects of vertical wall barrier. The vertical wall barrier can reduce deflection 34% and 74% for concentric and edge loadings respectively.

This paper is aimed to discuss the comparison of the slab deflection behavior between the Nailedslab with a vertical wall barrier and without a vertical wall barrier. The Nailed-slab models consider the vertical wall barrier on each end of the slab. The experimental study was conducted by full scale model tests of one row pile Nailedslab system and analyzed by finite element method.

### 2. INVESTIGATED 1-PILE ROW FULL SCALE NAILED-SLAB SYSTEM

Detail of the procedure on 1-pile row full scale Nailed-slab is presented in Puri, et.al. [4] and briefly described in Puri, et.al. [5]. In this paper, it will be presented again comprehensively.

### 2.1 Soil Pond and Materials

A full scale model of Nailed-slab was conducted on soft clay. A 6 m x 3.6 m soil pond was conducted by digging the existing soil until the depth of 2.5 m. On the two longer sides it was retained by masonry walls and supported by some temporarily bamboo girder. The anchorage system was built near the pond. Separator sheets were set on the pond walls and base to avoid the effects of surrounding existing soils. A 2.15 m of pond depth was filled by soft clay which was taken from District Ngawi, East Java, Indonesia. The soft clay properties are presented in Table 1. The slab and piles were reinforced concrete. The concrete strength characteristic of the slab and piles was 29.2 MPa and 17.4 MPa respectively. The flexural strength of the slab was 4,397.6 kPa.

### 2.2 Dimension of Nailed-slab Prototype

The Nailed-slab System Prototype dimension was 6.00 m  $\times$  3.54 m, 0.15 m in slab thickness, and the slab was reinforced by micro piles 0.20 m in diameter and 1.50 m in length. The spacing between piles was 1.20 m. This model was obtained by cutting the 600 cm  $\times$  354 cm  $\times$  15 cm Nailed-slab to 3 parts where each part consisted of one pile row. The tested 1 pile row Nailed-slab was the middle one with slab dimension 600 cm  $\times$ 120 cm  $\times$  15 cm as shown in Figure 2. All piles were installed under the slab and connected monolithically by using thickening slab connectors  $(0.40 \text{ m} \times 0.40 \text{ m} \text{ and } 0.20 \text{ m} \text{ in thickness})$ . Each end of slab is equipped by the vertical concrete wall barrier. There was a 5 cm lean concrete thickness under the slab. The slab was loaded by compression loadings with different load positions. Loads were transfered to the slab surface by using a circular plate 30 cm in diameter (the plate represents the wheel load contact area). Then the instrumentations were recorded. Details about testing procedure is presented in Puri, et.al. ([4],

[5]).

Table 1 Soft clay properties [4]

Parameter	Unit	Average
Spesific gravity, $G_{\rm s}$	-	2.55
Consistency limits:		
- Liquid limit, <i>LL</i>	%	88.46
- Plastic limit, PL	%	28.48
- Shrinkage limit, SL	%	9.34
- Plasticity index, PI	%	59.98
- Liquidity index, LI	%	0.36
Water content, w	%	54.87
Clay content	%	92.93
Sand content	%	6.89
Bulk density, γ	kN/m <sup>3</sup>	16.32
Dry density, $\gamma_d$	kN/m <sup>3</sup>	10.90
Undrained shear strength, $s_{\rm u}$		
- Undisturbed	kN/m <sup>2</sup>	20.14
- Remolded	kN/m <sup>2</sup>	11.74
CBR	%	0.83
Soil classification:		
- AASHTO	-	A-7-6
- USCS	-	CH

### **2.3 Analysis of Deflections**

In the 2D finite element analysis (FEM), Mohr-Coulomb soil model was employed in the study. Likewise, soil parameters and idealization of structural elements are presented in Table 2 and 3, respectively. The material properties were adjusted due to the plain strain case [6]. The slab width is 120 cm and the length of considered section is 20 cm (perpendicular to cross section). Numerical analysis was conducted by 2D Plaxis version 8.6. The soft clay was modeled by Mohr-Coulomb in undrained condition. All structural elements were modeled by plate element in linear-elastic behavior. Lean concrete was modeled by soil with linear-elastic non-porous material. The thickening slab was ignored since it could not be modeled by numerical application program.

The used mesh in plain strain FEM analysis is shown in Fig. 3. Fig. 4 shows one of deformed shape outputs.



b). Cross section

Fig. 2 Schematic diagram of full scale Nailed-slab with 1 pile row

Parameters	Name/ Notation	Soft clay	Sand	Unit
Material model	Model	Mohr-Coulomb	Mohr-Coulomb	-
Material behavior	Туре	Undrained	Drained	-
Saturated density	X <sub>sat</sub>	16.30	18.00	kN/m <sup>3</sup>
Dry density	X <sub>d</sub>	10.90	20.00	kN/m <sup>3</sup>
Young's Modulus	Ε	1,790.00	42,750.00	kPa
Poisson's ratio	V	0.45	0.35	-
Undrained cohesion	Cu	20.00	1.00	kPa
Internal friction angle	w1	1.00	47.80	0
Dilatancy angle	Œ1	0.00	2.00	0
Initial void ratio	$e_0$	1.19	0.50	-
Interface strength ratio	R	0.80	0.70	

Table 2 Model and parameters of soil

Parameters	Name/	Lean concrete	Structural elements			Unit
	Notation	(LC)	Slab	Vertical	Pile	
				wall barrier		
Material model	Model	Volume	Plate	Plate	Plate	-
		element				
Material behavior	Туре	Elastic	Elastic	Elastic	Elastic	-
Normal stiffness	$E\!A$	-	4,554,000	3,795,000	616,696	kN/m
Flexural rigidity	EI	-	8,539	4.941	75,655	kNm²/m
Equivalent thickness	d	-	0.15	0.125	0,027	m
Weight	W	-	3.60	3.00	29.12	kNm/m
Poisson's ratio	v	0.2	0.15	0.15	0.20	-
Density	x1	22	24	24	24	kN/m <sup>3</sup>
Young's Modulus	E	17,900	25,300	25,300	19,600	$MN/m^2$
Interface strength ratio	R	0.80	0.80	0.80	0.80	-

Table 3 Model and parameters of structural elements in FEM 2D plain strain



Fig. 3 A used mesh in plain strain FEM analysis.



Fig. 4 A deformed shape output of numerical analysis for edge loading

### 3. RESULTS AND DISCUSSION

### 3.1 *P*-u Relationship for Nailed-Slab with Vertical Wall Barrier

Fig.5 shows deflection shape along the slab (cross section in field condition). It is seen that the deflection shape is a bowl shape. Analysis results show that maximum displacement occured under the loading point and decreased as you move further away from the loading point. This phenomenon fulfilled the expectation. The maximum deflections were appropriate with the observations. But the end of slab was uplifted. Both ends of the slab were uplifted for concentric loading (Fig. 5a). However, the opposite end of the slab was uplifted caused by edge loading (Fig. 5b).



Fig. 5 Deflection shape along the slab for load P = 80 kN; a) concentric load, b) edge load

According to Figure 6, the maximum shear between soil and pile occured around the pile tip of the middle piles (Fig. 6a) and the left pile for edge loading (Fig. 6b). The extreme shear stresses on pile were 12.63 kN/m<sup>2</sup> and 10.46 kN/m<sup>2</sup> for concentric loading and edge loading, respectively. Both shear stresses did not reach the ultimate value of 16.00 kN/m<sup>2</sup> (= $R_{inter}c_u$ ).



Fig. 6 Shear stress on the interface of structural elements; a) concentric load, P = 150 kN, b) edge load, P = 80 kN

### 3.2 Effects of Vertical Wall Barrier

Figure 7 shows the P- $\delta$  relationship for edge loading. It seems that the vertical wall barrier can reduce deflection 5.25% only. It is an insignificant reduction if it is compared to the model test. The vertical wall barrier can reduce 74% deflection for edge loadings in the model test [1].



Fig. 7 P-ulrelationships for load on C (edge load)

### 4. CONCLUSION

In this paper, observations for pavement of Nailed-slab System which are equiped by vertical wall barrier on the end of slab were conducted and numerical analysis for both systems with and without vertical wall barrier has been done. Numerical results show that the vertical wall barrier gave insignificant reduction to the slab deflection. It is opposite to the model test result from Puri, et.al. [1] where the vertical wall barrier can reduce 74% deflection for edge loadings. Soil shear stresses did not reach the ultimate value for both load positions.

### 5. ACKNOWLEDGEMENTS

The authors acknowledge the financial support from the Directorate General of Research and Technology and Higher Education Republic of Indonesia number SP DIPA-042.06.401516/2016.

### 6. REFERENCES

- Puri, A., Hardiyatmo, H.C., Suhendro, B., and Rifa'i, A., 2011, Contribution of Wall Barrier to Reduce the Deflection of Nailed-Slab System in Soft Clay, Proc. of 9<sup>th</sup> Indonesian Geotech. Conf. and 15<sup>th</sup> Annual Scientific Meeting (KOGEI IX & PIT XV) HATTI, HATTI, Jakarta, 7-8 December 2011, pp. 299-306 (in Bahasa Indonesia).
- [2] The Indonesian Research and Development Center for Highway and Bridge, 2007, Uji Coba Skala Penuh Teknologi Cakar Ayam Modifikasi, Bab-7 Gambar Rencana, Satuan Kerja Pusat Litbang Jalan dan Jembatan, Departemen Pekerjaan Umum Republik Indonesia.
- [3] Suhendro, B., dan Hardiyatmo, H.C., 2010, Modified Chicken Foot Pavement System as an Alternative Solution for Road Construction on Soft Soils, Expansive, and Embankment, *Proc. of One Day Seminar and Exhibition* 2010 New Innovative Technology on Highway and Bridge, DPD HPJI Jatim, Surabaya, 31 March 2010 (in Bahasa Indonesia).
- [4] Puri, A., Hardiyatmo, H.C., Suhendro, B., and Rifa'i, A., 2013, Behaviour of Full scale Nailed-slab System with Variation on Load Positions, Proc. 1<sup>st</sup> Intl. Conf. on Infrastructures Development (ICID), Surakarta, 1-3 November 2013, pp. 26-36.
- [5] Puri, A., Hardiyatmo, H.C., Suhendro, B., and Rifa'i, A., 2014, Behavior of Nailed-slab System on Soft Clay Due to Repetitive Loadings by Conducting Full Scale Test, *IJCEE-IJENS*, Vol. 14 No. 06, pp. 24-30.
- [6] Plaxis 3D Foundation, *Material Models Manual version 1.5.*

Copyright © Int. J. of GEOMATE. All rights reserved, including the making of copies unless permission is obtained from the copyright proprietors.



# International Journal of GEOMATE

A Scientific International Journal on Geotechnique. Construction Materials and Environment

## PUBLISHING AGREEMENT

Dear Sir,

I am required to obtain copyright of papers from authors for the term of copyright and I would be grateful if you would confirm your acceptance by signing and returning the agreement below. I will not withhold permission for any reasonable request from you to publish any part of this paper in connection with any other work by you, original provided the usual acknowledgements are given regarding copyright notice and reference to the publication. If it is appropriate, the author's employer may sign this agreement and, in any event, the employer may reserve the right to use the paper internally or for promotional purposes only by indicating to this agreement.

E excerpts from copyrighted works are included, the author will obtain written permission from the copyright owners and show credit to the sources in the manuscript). The author also warrants that the article contains no The author warrants that the manuscript is the author's original work and has not been published before libellous or unlawful statements and does not infringe on the rights of others. If the work was prepared jointly the author agrees to inform co-authors of the terms of the agreement and to sign on their behalf.

Editors-in-Chief

Name of the Journal:



A Scientific International Journal on Geotechnique. Construction Materials and Environment

I hereby assign the copyright to my paper entitled,

SCALE 1-PILE ROW NAILED-SLAB SYSTEM ON SOFT SUB GRADE BY COMPRESSION LOADINGS EFFECTS OF VERTICAL WALL BARRIER DUE TO RIGID PAVEMENT DEFLECTION OF FULL +note -

if the paper is rejected, this assignment is null and void

Name of author: ANAS PURJ

Signature:

October 7th, 2016 Date: Please send this form duly filled and signed together with your manuscript to:

Professor, Division of Environmental Science and Technology Graduate School of Bioresources, Mie University Dr. Zakaria Hossain, Editor-in-Chief E-mail: zakaria@bio.mie-u.ac.jp Tsu-city, Mie 514-8507, Japan 1577 Kurima Machiya-cho Tel: +81-59-231-9578 Fax: +81-59-231-9578



### PUBLISHING AGREEMENT

Dear Sir,

I am required to obtain copyright of papers from authors for the term of copyright and I would he grateful if you would confirm your acceptance by signing and returning the agreement below. I will not withhold permission for any reasonable request from you to publish any part of this paper in connection with any other work by you, provided the usual acknowledgements are given regarding copyright notice and reference to the original publication. If it is appropriate, the author's employer may sign this agreement and, in any event, the employer may reserve the right to use the paper internally or for promotional purposes only by indicating to this agreement. The author warrants that the manuscript is the author's original work and has not been published before (if excerpts from copyrighted works are included, the author will obtain written permission from the copyright owners and show credit to the sources in the manuscript). The author also warrants that the article contains no libellous or unlawful statements and does not infringe on the rights of others. If the work was prepared jointly the author agrees to inform co-authors of the terms of the agreement and to sign on their behalf.

Editors-in-Chief

Name of the Journal:



Ascientific International Journal on Godedmique, Construction Materials and Environment,

I hereby assign the copyright to my paper entitled,

EFFECTS OF VERTICAL WALL BARRIER DUE TO RIGID PAVEMENT DEFLECTION OF FULL SCALE 1-PILE ROW NAILED-SLAB SYSTEM ON SOFT SUB GRADE BY COMPRESSION LOADINGS +note

of the paper is rejected, this assignment is null and void

Name of author: AHMAD RIFA'I

Signature:

Date: October 14 , 2016

Please send this form duly filled and signed together with your manuscript to:

Dr. Zakaria Hossain, Editor-in-Chief Professor, Division of Environmental Science and Technology Graduate School of Bioresources, Mie University 1577 Kurima Machiya-cho Tsu-city, Mie 514-8507, Japan E-mail: zakaria@bio.mie-u.ac.jp Tel: +81-59-231-9578 Fax: +81-59-231-9578



# International Journal of GEOMATE

A Scientific International Journal on Geotechnique, Construction Materials and Environment

## PUBLISHING AGREEMENT

Dear Sir,

would confirm your acceptance by signing and returning the agreement below. I will not withhold permission for any reasonable request from you to publish any part of this paper in connection with any other work by you, I am required to obtain copyright of papers from authors for the term of copyright and I would be grateful if you provided the usual acknowledgements are given regarding copyright notice and reference to the original publication. If it is appropriate, the author's employer may sign this agreement and, in any event, the employer may reserve the right to use the paper internally or for promotional purposes only by indicating to this agreement. The author warrants that the manuscript is the author's original work and has not been published before (if excerpts from copyrighted works are included, the author will obtain written permission from the copyright owners and show credit to the sources in the manuscript). The author also warrants that the article contains no libellous or unlawful statements and does not infringe on the rights of others. If the work was prepared jointly the author agrees to inform co-authors of the terms of the agreement and to sign on their behalf.

Editors-in-Chief

Name of the Journal:



## International Journal of GEOMATE

A Scientific International Journal on Geotechnique. Construction Materials and Environment

I hereby assign the copyright to my paper entitled,

SCALE 1-PILE ROW NAILED-SLAB SYSTEM ON SOFT SUB GRADE BY COMPRESSION LOADINGS EFFECTS OF VERTICAL WALL BARRIER DUE TO RIGID PAVEMENT DEFLECTION OF FULL +note -

if the paper is rejected, this assignment is null and void

Name of author: BAMBANG SUHENDRO

Signature:

Date: October , 2016

Please send this form duly filled and signed together with your manuscript to:

Dr. Zakaria Hossain, Editor-In-Chief Professor, Division of Environmental Science and Technology Graduate School of Bioresources, Mie University 1577 Kurima Machiya-cho Tsu-city, Mie 514-8507, Japan E-mail: zakaria@bio.mie-u.ac.Jp Tel: +81-59-231-9578 Fax: +81-59-231-9578